

PRIMARY CORNER DESCRIPTION Standard Cor. Secs. 2 & 3 only, T23-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1495)

Set standard cor. to secs. 2 and 3, from which
A Fir 24" dia., bears S.15°W., 10 lks. dist.
A Dogwood 4" dia., bears S.50°E., 10 lks. dist.

GLO survey by W.H. Byars, Deputy Surveyor under contract # 376 survey dated Jan 22, 1881 (DCSO records Vol. 4 Page(s) 1535)

Old cor., bearing trees standing, set new post as per instructions, from which a
Fir tree 24" dia., bears S.15°W., 10 lks. dist.
Dogwood 4" dia., bears S.50°E., 30 lks. dist.

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Joint contract #664 dated May 23, 1896 (DCSO records Vol. 4 Page(s) 1540)

Standard cor. of secs. 2 and 3, T23-7, post destroyed; I reestablish this cor. from the bearing trees as follows:
Set a Sandstone 14 x 12 x 5 ins., 9" in the ground for a standard cor., mkd. S C on S., with 2 grooves on E., and 4 grooves on W. faces; from which
A Fir 24" dia., bears S.15°W., 10 lks. dist. mkd. T23S R7W S3 BT.
A Dogwood 6" dia., bears S.50°E., 30 lks. dist. mkd. T23S R7W S2 BT.

Wilford N. Haines - For: E.G. Whipple - Oct. 1957 - M 1-59

Set 1" x 1" x 36" Iron rod with brass cap inscribed "Wilford N. Haines #239 Survey Point".
Found - SW BT and 10" Fir S.65°E., 29.5 ft.

Wilford N. Haines - For: E.G. Whipple Mill - March/April 1960
M 18-33

Found - 1" x 1" x 36" T Iron.
Orig. SW BT.
New BT - 10" Fir S.65°E., 29.5 ft.

BLM resurvey by Wayne L. Rogers and Lance J. Bishop, Cadastral Surveyors, under Group #1160, surveyed April/July 1984 - (DCSO records Vol. 47 Page(s) 18069)

(Cont. Next Page)

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 507100

PRIMARY CORNER DESCRIPTION Standard cor. secs. 2 & 3 only, T23-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

The standard cor. of secs. 2 and 3, perpetuated and recorded by Haines in 1957, monumented with a 1" T shaped iron rod, firmly set, projecting 6" above ground, from which the remains of an original bearing tree:

A root hole bears S.15°W., 10 lks. with a down Fir lying down hill, 35" dia., no marks visible.

and the remains of a bearing tree mkd. by Haines

A root hole bears S.65°E., 45 lks. dist., with a sawed Fir stump lying alongside, 20" dia., with scribe marks W S2 BT visible on opened blaze.

At the corner point

Set an iron post, 16" long, 5/8" dia., cemented 8" in bedrock, with alum. cap 1½" dia., mkd.

S 3 S 2
S C
T 23 S R 7 W
1984

from which a bearing object and a new bearing tree

A rock outcrop 4 x 3 x 3 ft. bears S.58 3/4°E., 97 lks. dist. mkd. X BO.

A Fir 13" dia., bears S.17 3/4°W., 58 lks. dist. mkd. T23S R7W S3 SC BT.

Deposit T shaped iron rod alongside the corner.