

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 35

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Wilford N. Haines, #239 - For: E.G. Whipple - Oct. 1957 -
C.S. File 42/309 and M 1-59

Set 1" x 1" x 36" Iron rod with brass cap inscribed "Wilford
N. Haines 239 Survey Point"
12" Fir S.44°E., 26.0 ft.
44" Fir N.84°W., 10.0 ft.

BLM resurvey by Wayne L. Rogers and Lance J. Bishop,
Cadastral Surveyors, under Group #1160, surveyed April/July
1984 - (DCSO records Vol. 47 Page(s) 18085-86)

The center ¼ sec. cor. of sec. 35, established and recorded
by Haines in 1957, and is accepted as the corner, monumented
with a 1" T shaped iron rod, firmly set, projecting 4" above
ground, with a washer, 1" dia., mkd. WILFORD N HAINES

239
SURVEY POINT
DRAIN OREGON

from which bearing trees mkd. by Haines

A Fir 18" dia., bears S.47 3/4°E., 38 lks. dist. with
healed blaze.

A Fir 53" dia., bears N.84 3/4°W., 15 lks. dist. with
scribe marks C 1/4 S35 BT visible on bark blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 20" in the ground,
directly over iron rod, in a mound of stone, 3 ft. base, to
top, with brass cap mkd:

T 22 S R 7 W
C 1/4 S 35
1984

From this point, U.S. Geological Survey triangulation station
"BELL MOUNTAIN 1953 1980" bears N.0°14'W., 14.26 chs. dist.,
monumented with a concrete post, 1 ft. dia., firmly set,
projecting 4" above ground, with standard brass tablet, 3½"
dia., mkd. BELL MOUNTAIN 1953 1980 and a triangle.