

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 35

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO records Vol. 4 Page(s) 1539)

Set a Hemlock post, 3 ft. long, 4" sq., 24" in the ground, for 1/4 sec. cor., mkd. 1/4 S on N. face; from which
A Fir 18" dia., bears N.2°E., 24 lks. dist. mkd. 1/4 S BT.
A Fir 16" dia., bears S.60°W., 34 lks. dist. mkd. 1/4 S BT.
This cor. is on the Westerly slope of mountain, 75 ft. above creek.

Wilford N. Haines, #239 - For: E.G. Whipple - Oct. 1957 - C.S. File 42/309 and M 1-59

Original BTs, both snags.
40" Fir N.2°W., 56.5 ft.
12" Fir S.11°45'E., 81.0 ft.
Set 1" x 1" x 36" Iron rod with brass cap inscribed "Wilford N. Haines #239 Survey Point".

BLM resurvey by Wayne L. Rogers and Lance J. Bishop, Cadastral Surveyors, under Group #1160, surveyed April/July 1984 - (DCSO records Vol. 47 Page(s) 18086)

The 1/4 sec. cor., perpetuated and recorded by Haines in 1957, monumented with a 1" T shaped iron rod, firmly set, projecting 4" above ground, from which the remains of an original bearing tree:
A Fir snag 20" dia., bears S.60°W., 34 lks. dist. with healed blaze.
and a bearing tree mkd. by Haines:
A Fir 46" dia., bears N.3°W., 86 lks. dist., with healed blaze.
At the corner point
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, directly over iron rod, with brass cap mkd: T 22 S R 7 W
1/4 S 26
S 35
1984
from which a new bearing tree:
A Hemlock 16" dia., bears S.25°E., 31 lks. dist. mkd. 1/4 S35 BT.

Found OK, Oct. 1995 by Hoffine - M119-78