

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 4 Page(s) 1532)

Set ¼ sec. post, from which
A Fir 12" dia., bears S.65°E., 48 lks. dist.
A Cedar 24" dia., bears N.75°W., 35 lks. dist.

Wilford N. Haines, #239 - For: E.G. Whipple - Oct.1957 - C.S. file 42/309 and M 1-59

Set 1" x 1" x 36" I.Rod with brass cap inscribed Wilford N. Haines #239 Survey Point.
8" Fir N.44°W., 19.3 ft.
60" Incense Cedar S.17°W., 32.7 ft.

BLM resurvey by Wayne L. Rogers and Lance J. Bishop, Cadastral Surveyors, under Group #1160, surveyed April/July 1984 - (DCSO records Vol. 47 Page(s) 18079)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:
T 22 S R 7 W
1/4 S 23
S 26
1984

from which
A Fir 9" dia., bears S.54°E., 6½ lks. dist. mkd. ¼ S26 BT.
A Fir 4" dia., bears N.28½°W., 17 lks. dist. mkd. X BT.