

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 23

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 4 Page(s) 1517)

-----  
Set ¼ sec. post, from which  
A Fir 8" dia., bears N.31°E., 83 lks. dist.  
A Fir snag 40" high 40" dia., bears S.40°W., 48 lks.

J. W. Cole, Deputy - Wit: John, Jim and Oscar Hancock - Vol. 2 Page 245 - Dec. 1915

-----  
Renew corner from Fir witness tree and remains of snag called for in field notes.  
Set a 4" x 4 ft. Fir post, from which  
An orig. BT, a Fir 24" dia., bears N.31°E., 83 lks.  
An Oak 10" dia., bears S.44°15'E., 150 lks. dist.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy and C. Putnam, crew - June 4, 1962 - C.S. File 52/14-9

-----  
Found - Haines "T" iron and cap. (Unrecorded)  
63" Fir N.31°E., 54.8 ft. Orig. calls for 8" Fir N.31°E., 54.8 ft. This tree recently bark scribed "¼ S14 363 BT".  
20" B.Oak S.38°E., 99.0 ft. cut open, tree hollow, has been cut open several years ago and all marks, if any, are rotted away. Cole calls for 10" Oak, S.44¼°E., 99.0 ft.  
Stump hole with some old Fir bark still in place, S.40°W., 38.3 ft.

BLM resurvey by John M. Jelley and Donald Beck, Cadastral Surveyors, under Group #590, surveyed July/Aug. 1965 (DCSO records Vol. 33 Page(s) 13953)

-----  
The ¼ sec. cor., perpetuated and recorded by Haines in 1958, monumented with a 1" T Iron, firmly set, extending 12" above the ground, with brass disc mkd. Wilford N. Haines 239 Survey Point, Drain Oregon, from which the original bearing trees:  
A Fir 64" dia., bears N.31°E., 83 lks. dist. no orig. scar evident, has been remarked, scribe marks ¼ S14 363 BT visible on bark blaze.  
The stump hole of a Fir bears S.40°W., 48 lks. dist.  
And a bearing tree mkd. by Cole in 1913  
A B.Oak 20" dia., bears S.41 ¾°E., 150 lks. dist., with opened double blaze, no marks remaining.  
At the corner point  
(Cont. Next Page)

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground,  
with brass cap mkd:

T 22 S R 7 W

1/4 S 14  
S 23

1965

from which a new bearing tree

A Fir 4" dia., bears S.43°E., 8 lks. dist., mkd. X BT.

Deposit T iron alongside the iron post.

Fd. OK, BLM survey by Rogers and Bishop under Group #1160,  
surveyed April/July 1984 (DCSO records, Vol. 47 Pg 18081-82)

Fd. OK, April 1993, K. Hoffine, M 117-4

BLM dependent resurvey by Jeffrey O. Covington, Cadastral  
Surveyor, under Group No. 2824, surveyed May 2016/March 2018  
- (DCSO records Vol. 59 Page(s) 23890)

-----  
The 1/4 sec. cor. of secs. 14 and 23, monumented with an iron  
post, 2 1/2" dia., firmly set, projecting 4" above ground  
(alongside of which is a "T" shaped iron rod 3/4" dia.,  
firmly set, projecting 12" above ground, with brass washer  
mkd. WILFORD N. HAINES SURVEY 239 DRAIN, ORE., with a tack in  
center), with brass cap (properly) mkd.

from which the remains of an original bearing tree reported  
by Jelley and Beck in 1965

A sawed decayed fir stump 67" dia., bears N.31°E., 54.8  
ft., with scribe marks BT visible on bark.

and the remains of the bearing tree mkd. by Cole, in 1915

A root hole bears S.41 1/4°E., 99.0 ft., alongside of which  
is a down decayed oak log, size indeterminate, with no  
marks visible.

and new bearing trees

A fir, 7" dia., bears N.7 1/4°E., 12.6 ft., mkd. 1/4 S14 BT.

A fir, 6" dia., bears S.81°W., 14.2 ft., mkd. 1/4 S23 BT.

Each new BT has a 2 1/2" x 1/4" magnetic nail (Mag Nail) driven at  
the base right side-center & each monument established or  
remonumented has a magnet deposited in a white plastic case  
at the base of the stainless steel post. Alum. angle iron  
driven alongside each monument.