

PRIMARY CORNER DESCRIPTION Center 1/4 Cor for Sec 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

J.W. Cole - Deputy - For: John Hancock - Dec. 1915 - Vol. 2
Page 246 and Field Book 64 Pages 7-25

Set 4" x 4" x 3½ ft. Cedar post mkd. ¼ Sec., from which
Oak 30" mkd. "¼ Sec BT" bears N.54°30'W., 27 lks.
Oak 30" mkd. "¼ Sec BT" bears N.28°E., 216 lks.
No other trees near. (1993 & 2016 renewals)

Wilford N. Haines - Filed March 1964 (work done prior to
1961) - C.S. File 51/282

Set 1" x 1" x 36" T iron with brass cap.
Found - 30" Oak N.54°30'W., 17.82 ft.
30" Oak N.28°00'E., 142.56 ft.
(These BTs presumable marked by J.W. Cole, Deputy, in Dec.
1915. See Vol. 2 Page 245-46 for record.) (1993 & 2016
renewals)

Ken Hoffine - For - Lone Rock Timber Co. - April 1993 - M
117-4.

Set - 5/8"x40" I.R. with 2½" aluminum cap mkd. "Lone Rock
Timber T22S R7W C 1/4 S 14".
4" D.Fir, bears S.20°E., 4.81 ft. I scribe C1/4 S14 BT
and tag.
4" D.Fir, bears S.34½°W., 31.3 ft. I scribe C1/4 14 BT
and tag.
44" Oak, bears N.59½°W., 33.18 ft. I scribe C1/4 S14 BT
and tag. (This oak tree is also bearing tree for
Haines T-Iron).
4" D.Fir, bears N.14°E., 34.00 ft. I scribe C1/4 S14 BT
and tag.
T-Iron by Haines for Coles 1915 survey Vol. 2 Pg. 245-46
bears N. 51°02'W., 14.84'.
Corner lies on gentle slope with 3" to 4" DBH Reprod to south
& northeast. Grass field to northwest.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral
Surveyor, under Group No. 2824, surveyed May 2016/March 2018
- (DCSO records Vol. 59 Page(s) 23905)

The center ¼ sec. cor. of sec. 14, established by Hoffine, in
1993, and is accepted as the cor monumented with an iron rod,
5/8" dia., 38" long, firmly set, projecting 5" above ground,
with aluminum cap mkd. LONE ROCK TIMBER T 22 SR7WC 1/4 S 14
1993 PLS 2291

continued next page

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 540440

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the bearing trees mkd. by Hoffine
A fir, 15" dia., bears N.14 $\frac{1}{4}$ °E., 33.9 ft., with a healed blaze.
A fir, 15" dia., bears S.18 $\frac{3}{4}$ °E., 4.3 ft., with a healed blaze.
A fir, 13" dia., bears S.34 $\frac{1}{2}$ °W., 81.7 ft., with a healed blaze.
An oak, 50" dia., bears N.59 $\frac{1}{2}$ °W., 33.6 ft. with no marks visible on partially opened blaze.

At the corner point
Set a stainless steel post, 28" long, 2 $\frac{1}{2}$ " dia., 26" in the ground, directly over the iron rod with brass cap mkd.

T 22 S R 7 W
C $\frac{1}{4}$ S 14
2016

From this cor. a point erroneously established as the center 1/4 sec. cor. of sec. 14 by Cole, Deputy County Surveyor, in 1915, perpetuated by Haines, in 1964, bears N.51°20'47"W., 14.83 ft., monumented with a "T" shaped iron rod, 3/4" dia firmly set, projecting 14" above ground. This point was not correctly positioned and was not utilized for control in this survey,
from which the bearing tree mkd. by Cole
An oak, 50" dia., bears N.65 $\frac{3}{4}$ °W., 19.0 ft. with no marks visible on partially opened blaze.