

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 4 Page(s) 1519)

Set ¼ sec. post, from which
A Fir 14" dia., bears N.40°E., 42 lks. dist.
A Fir 48" dia., bears S.60°E., 26 lks. dist.

J.W. Cole - Dec. 1915 - Vol. 2 Page 245 (and "old" corner book, page 22)

Renew corner from orig. witness tree, a Fir 48" dia.
Set a 3" x 4" x 4 ft. Chinquapin post and mark:
A Fir 30" dia., N.46°E., 56 lks. dist.

Wilford N. Haines - For: Woolley Logging Co. - Sept. 1960 - M 11-72 (also on work filed March 1964, C.S. File 51/282)

Found - 48" Fir S.60°E., 26 lks., down.
Hole in ground for 30" Fir, N.46°E., 56 lks.
Set 1" x 1" x 36" T iron.
Scribe - 14" Fir S.41½°W., 16.9 ft.
14" Fir N.07°W., 28.0 ft.

BLM resurvey by John M. Jelley and Donald Beck, Cadastral Surveyors, under Group #590, surveyed July/Aug. 1965 (DCSO records Vol. 33 Page(s) 13956-57)

The ¼ sec. cor., perpetuated and recorded by Haines in 1960, monumented with a 1" T Iron, firmly set, extending 3" above the ground, with brass disc mkd. Wilford N. Haines 239 Survey Point Drain Oregon, from which the remaining original BT:
A down and rotted Fir 48" dia., bears S.50°E., 28 lks. dist., with no marks remaining. (Rec. S.60°E., 26 lks.)
and a bearing tree mkd. by Cole in 1915
A rotted Fir stump, size indeterminate, bears N.41°E., 60 lks. dist.
and bearing trees mkd. by Haines
A Fir 22" dia., bears N.6 3/4°W., 43 lks. dist. with partly healed double blaze.
A Fir 22" dia., bears S.42°W., 26 lks. dist. with partly healed double blaze.

At the corner point
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 22 S R 7 W
¼ $\frac{S \ 11}{S \ 14}$
1965

(Cont. Next Page)

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which new bearing trees
A Fir 23" dia., bears N.10°E., 64 lks. dist. mkd. ¼ S11 BT
A Fir 11" dia., bears S.3¼°W., 63½ lks. dist. mkd. ¼ S14 BT.
Deposit T iron alongside the iron post.

Fd. OK, April 1993, K. Hoffine, M 117-4

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2824, surveyed May 2016/March 2018 - (DCSO records Vol. 59 Page(s) 23898-9)

The ¼ sec cor. of secs. 11 and 14, monumented with an iron post, 2½" dia., firmly set, projecting 2" above ground with brass cap (properly) mkd.
from which the bearing trees mkd by Haines, in 1960, reported by Jelley and Beck in 1965
A fir, 35" dia., bears S.42°W., 17.2 ft., with a healed blaze.
A fir, 30" dia., bears N.6¾°W., 28.4 ft, with a healed blaze.
and the bearing trees mkd. by Jelley and Beck
A fir, 26" dia., bears N.10°E., 42.2 ft., with a healed blaze.
A fir, 20" dia., bears S.3¼°W., 41.9 ft., with a healed blaze.