

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 540540

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Secs. 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Wilford N. Haines, L.S. #239 - For: Woolley Logging Co. -
Sept. 1960 - M 11-72

Set 1" x 1" x 36" T. iron.
Scribe - 36" Fir S.05°W., 39.0 ft.
20" Fir S.50°E., 75.7 ft.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral
Surveyor, under Group No. 2824, surveyed May 2016/March 2018
- (DCSO records Vol. 59 Page(s) 23899)

The center ¼ sec. cor. of sec. 11, established by Haines, in
1960, and is accepted as the cor. monumented with a "T"
shaped iron rod, 3/4" dia, firmly set, projecting 9" above
ground, with brass washer mkd. WILFORD N. HAINES 239 SURVEY
POINT DRAIN, ORE. with a tack in center,
from which the bearing trees mkd. by Haines

A fir, 36" dia., bears S.52¼°E., 75.5 ft., with a healed
blaze.

A fir, 52" dia., bears S.3¾°W., 38.5 ft., with a healed
blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 23" in the
ground, directly over the iron rod, 38 ins. long with brass
cap mkd.

T 22 S R 7 W

C ¼ S 11

2016