

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 11 (WC)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 4 Pg 1520)

Set ¼ sec. post, from which
A Fir 26" dia., bears N.38°W., 18 lks. dist.
A Fir 48" dia., bears S.65°W., 96 lks. dist.

O.F. Thiel - For: Carl Binder - April 1943 - Field Book 117 Page 96

No trace of old cor. to be found. Marked a Cedar 6", East of corner.

Wilford N. Haines - For: Woolley Logging Co. - Sept. 1960 - M 11-72

Set 1" x 1" x 36" T. Iron.
Scribe - 20" Cedar S.14°E., 45.5 ft.
16" Maple N.25°E., 42.6 ft.

Douglas Co. Surveyors Office - L.E. Monrean; R.B. Kimberling, crew - April 25, 1977 - C.S. File 59/31-30

Found - Haines 1" T Iron NOT FOUND. Corner falls on NW edge of road.
A R.Cedar 20" now 28" bears S.14°E., 45.5 ft. Large log covers blaze portion of tree.
A Maple 16" now 18" bears N.25°E., 42.6 ft. Tree is double blazed partially healed, scribing visible "¼ S2 BT"

Set temporary point at ¼ corner as determined by Haines, from which we measure West 17.0 ft. to witness corner.

Set Brass cap at WITNESS CORNER mkd. "Douglas County Surveyor T22S R7W Wit. Cor. East 17.0 ft. to ¼ S2 S11 1977"

Set Witness post and sign 12 ft. West of Wit. Cor. monument. This monument is set in a mound of stone at the base of cut bank along NW edge of road.

New Accessories -

A D.Fir 30", bears N.25½°E., 14.4 ft. Tree double blazed and scribed "WC ¼ S2 CS BT".

Chiseled "WC X" in rock on cut bank on NW edge of road. "X" bears S.75°W., 9.8 ft.

Ron Rice - June 2016 - Seneca Jones Timber Co. - C.S. 65/94-1

Found - 1977 Douglas Co. WC Brass cap bearing West 17.0' from true position.

continued next page

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 11 (WC)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

38" D.Fir bears N.25½°E., 14.4' - Healed face
"X" in sandstone bears S.75°W., 9.8'
Steel post adjacent to corner
The following accessories are reference to the true ¼ corner position -
45" R.Cedar bears S.14°E., 45.5' - healed face
30" Maple bears N.25°E., 42.6' - healed face

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2824, surveyed May 2016/March 2018 - (DCSO records Vol. 59 Page(s) 23892)

True point for the ¼ sec cor of secs 2 & 11, reestablished by Haines in 1960, by proportionate measurement, and perpetuated by Monrean in 1977, and is accepted as a careful and faithful reestablishment of the cor., located in a dirt road; there is no remaining evidence of the T iron set by Haines. Determined at the record bearing and distance from the witness cor. established by Monrean, from which the BTs mkd. by Haines
A maple, 18" dia., bears N.24½°E., 42.7 ft., with a healed blaze
A cedar, 40" dia., bears S.15°E., 45.8 ft., with a healed blaze.
From the true point, the off-line witness cor. for the ¼ sec. cor. of secs. 2 and 11, established by Monrean bears West, 17.00 ft. monumented with an iron post, 1¼" dia., firmly set, projecting 12" above ground, with brass cap (properly) mkd from which accessories mkd. by Monrean
A fir, 38" dia., bears N.27¾°E., 15.0 ft., with a healed blaze.
A boulder on the cut bank on the NW edge of the same dirt road, with exposed face 3 ft. wide, 18 ins. tall, bears S.76½°W., 9.8 ft., mkd. with a cross (X) chiseled on the exposed east face.
The witness cor. is located W., 24 ft., from the center of the same dirt road.
Note: Haines' reestablished position was verified using his record and the survey by Jelley and Beck in 1965.