

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1495)  
-----  
Set standard ¼ sec. post, from which  
A Fir 40" dia., bears S.45°E., 57 lks. dist.  
A Fir 5" dia., bears S.67°W., 31 lks. dist.

---

GLO survey by W.H. Byars, Deputy Surveyor under contract # 376 survey dated Jan 22, 1881 (DCSO records Vol. 4 Page(s) 1535)  
-----  
Qr. sec. cor., witness trees all standing viz:  
Fir tree 40" dia., bears S.45°E., 57 lks. dist.  
Fir tree 5" dia., bears S.67°W., 31 lks. dist.  
Set new cor. post as per instructions.

---

Wilford N. Haines - For: E.G. Whipple - M 1-59  
-----  
SW BT is sound. SE BT is snag.  
Set 1" x 1" x 36" T Iron rod inscribed "Wilford N. Haines 239 Survey Point"

---

BLM resurvey by Wayne L. Rogers and Lance J. Bishop, Cadastral Surveyors, under Group #1160, surveyed April/July 1984 - (DCSO records Vol. 47 Page(s) 18067)  
-----  
The standard ¼ sec. cor. of sec. 2, perpetuated and recorded by Haines in 1957, monumented with a 1" T shaped iron rod, firmly set, projecting 10" above ground, with a washer 1" dia., mkd. Wilford N. Haines 239 Survey Point Drain Oregon from which the remains of the original bearing trees  
A decayed Fir stump size indeterminate, bears S.40°E., 57 lks. dist., no marks visible. (Rec. S.45°E.)  
A sawed Fir stump 10" dia., bears S.70°W., 31 lks. dist., no marks visible. (Rec. S.67°W.)  
and the remains of bearing tree mkd. by Haines  
A Cedar snag 10" dia., bears N.6°W., 17½ lks. dist. with scribe marks ¼ S BT visible on open blaze.  
At the corner point  
Set an alum. post, 28" long, 2 1/2" dia., 26" in the ground, directly over iron rod, with alum. cap mkd.  

-----  
1/4 S 2  
S C  
1984

  
from which new bearing trees  
A Fir 4" dia., bears S.57 3/4°E., 37 lks. dist. mkd. X BT  
A Cedar 19" dia., bears S.40½°W., 19 lks. dist.