

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 574100

PRIMARY CORNER DESCRIPTION Standard Cor. for Secs. 1 & 2, T23-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 376 survey dated Jan 22, 1881 (DCSO records Vol. 4 Page(s) 1535)

-----  
Marked a Fir 8" dia., for the cor. to secs. 1 and 2, from which a  
Maple tree 6" dia., bears S.67°E., 32 lks. dist.  
Fir tree 8" dia., bears S.68°W., 22 lks. dist.

Wilford N. Haines - For: E.G. Whipple - 1957 - C.S. File 42/309 and M 1-59

-----  
Set from original bearing trees.  
Set 1" x 1" x 36" Iron rod with brass cap inscribed "Wilford N. Haines #239 Survey Point".

BLM resurvey by Wayne L. Rogers and Lance J. Bishop, Cadastral Surveyors, under Group #1160, surveyed April/July 1984 - (DCSO records Vol. 47 Page(s) 18066)

-----  
The standard cor. of secs. 1 and 2, perpetuated and recorded by Haines in 1957, monumented with a 1" T shaped iron rod, loosely set, projecting 12" above ground, from which the remains of bearing tree mkd. by Byars:

A root hole bears S.68°W., 22 lks. dist., with a down Fir alongside 26" dia., with healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, directly over iron rod, with brass cap mkd:

-----  
S 2 S 1  
S C  
T 23 S R 7 W  
1984

from which new bearing trees

A Fir 8" dia., bears S.7°E., 33 lks. dist. mkd. T23S R7W S1 SC BT.

A Hemlock 13" dia., bears S.8½°W., 79 lks. dist., mkd. T23S R7W S2 SC BT.