

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 35 and 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO records Vol. 4 Page(s) 1536)

Set a Cedar post, 3 ft. long, 4" sq., 24" in the ground for Qr. sec. cor. mkd. ¼ S on W. face, from which
A Cedar 12" dia., bears S.74°E., 38 lks. dist. mkd. ¼ S BT
A Cedar 14" dia., bears S.89°W., 68 lks. dist. mkd. ¼ S BT
This cor. is on N. slope of spur, 25 ft. below top.

Wilford N. Haines, #239 - For: E.G. Whipple - Oct. 1957 - C.S. File 42/309 and M 1-59

Set from original BTs.
Set 1" x 1" x 36" Iron rod with brass cap inscribed Wilford N. Haines #239 Survey Point.

BLM resurvey by Wayne L. Rogers and Lance J. Bishop, Cadastral Surveyors, under Group #1160, surveyed April/July 1984 - (DCSO records Vol. 47 Page(s) 18072-73)

The ¼ sec.cor., perpetuated and recorded by Haines in 1957, monumented with a 1" T shaped iron rod, firmly set, projecting 8" above ground, with a washer 1" dia., mkd. Wilford N Haines 239 Survey Point Drain Oregon.

from which the remains of the original bearing trees:
A Cedar 40" dia., bears S.74°E., 38 lks. dist., with healed blaze.
A Cedar snag 36" dia., bears S.89°W., 68 lks. dist., with fragmentary reverse scribe marks visible on opened blaze.

At the corner point
Set an alum. post, 28" long, 2 1/2" dia., 24" in the ground, directly over iron rod, with alum. cap mkd: T 22 S R 7 W
1/4
S 35 S 36
1984

from which a new bearing tree
A Hemlock 19" dia., bears N.59°W., 15 lks. dist. mkd. ¼ S35 BT.

FD. Ok by K.Hoffine, Feb. 1995 - C.S. File 63/161-27