

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 26, 35 and 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO records Vol 4 Pg 1536)

Set a Chinguapin post, 3 ft. long, 4" sq., 24" in the ground for cor. of secs. 25, 26, 35 and 36, mkd. T22S S25 on NE.; R7W S36 on SE.; S35 on SW.; and S26 on NW. faces; with one notch on S. and E. edges, from which

A Cedar 16" dia., bears N.45°E., 147 lks. mkd. T22S R7W S25 BT.

A dead Fir 16" dia., bears S.40°E., 50 lks. mkd. T22S R7W S36 BT.

A Fir 30" dia., bears S.29°W., 92 lks mkd. T22S R7W S35 BT

A Fir 36" dia., bears N.12°W., 88 lks mkd. T22S R7W S26 BT

This cor. is on the steep East slope of spur, 50 ft. above creek.

Wilford N. Haines, #239 - For: E.G. Whipple - Oct. 1957 - C.S. File 42/309 and M 1-59

Set from original BTs.

Set 1" x 1" x 36" Iron rod with brass cap inscribed "Wilford N. Haines #239 Survey Point".

Ken Hoffine, L.S. #2291 - For: Lone Rock Timber - Feb. 1995 - C.S. File 63/161-27

Found - 34" Cedar, rotten stump, bears N.41°E., 98.2' (Rec. N.45°E. 97.0')

53" D.Fir, bears S.29°W., 62.0' (rec. S.29°W., 60.7') well healed face & BLM tag.

51" D.Fir stump, bears N.18°18'W., 54.4' (rec. N.12°W., 58.1') we chopped out old scar & found orig. scribing

Set - BTs a 5/8"x40" I.R. w/2.5" aluminum cap, stamped: LONE ROCK TIMBER T22SR7W SECTIONS 26,25,35, & 36.

New BTs- 24" D.Fir, bears S.54°E. 17.8', scribed S36 BT & tag
23" D.Fir, bears N.70½°E. 7.8', scribed S25 BT & tag

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2824, surveyed May 2016/March 2018 - (DCSO records Vol. 59 Page(s) 23873-4)

The cor. of secs. 25,26, 35 and 36, perpetuated by Haines, in 1957; further perpetuated by Hoffine, in June 1995; monumented with an iron rod, 5/8" dia. firmly set, projecting 6" above ground, with aluminum cap mkd. LONE ROCK TIMBER T 22 S R 7 W S 26 S 25 S 35 S 36 1994 PLS 2291,

continued next page

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 26, 35 and 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

from which the remains of the original bearing trees
A sawed decayed fir stump, 34" dia., bears N.40½°E., 97.0 ft., with a healed blaze. (Record, cedar, N.45°E.)
A fir, 54" dia., bears S.29°W., 60.7 ft., with a healed blaze.
A sawed fir stump, 51" dia., bears N.18¾°W 54.7 ft., with illegible scribe marks visible on a partially opened blaze. (Record, N.12°W., 58.1 ft.)
and the remains of the bearing trees mkd. by Hoffine
A fir, 30" dia., bears N.74½°E., 7.9 ft. with a healed blaze.
A sawed decayed fir stump, 24" dia., bears S.49¾°E, 16.6 ft., with no marks visible on a partially opened blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, directly over the iron rod, 40" long, with brass cap mkd

T 22 S R7W

S26 | S25

S35 | S36

2016

from which new bearing trees

A hemlock, 14" dia., bears S.24¼°E., 44.6 ft., mkd. T22S R7W S36 BT.

A hemlock, 8" dia., bears N.55¼°W., 27,9 ft., mkd. T22S R7W S26 BT,

NAD 1983 (2011)

Latitude: 43°37'12.03 N. Longitude: 123°29'05.35" W.