

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 600220

PRIMARY CORNER DESCRIPTION So. 1/16 Cor. bet. Secs. 25 and 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Wilford N. Haines, #239 - For: E.G. Whipple - Oct. 1957 -
C.S. File 42/309 and M 1-59

Set 1" x 1" x 36" Iron rod with brass cap inscribed "Wilford
N. Haines #239 Survey Point".
18" Fir N.49°30'E., 31.5 ft.
14" Fir N.39°W., 20.4 ft.

Douglas Co. Surveyors Office -R. B. Kimberling, Deputy- S.C.
Silagy, crew - May 15, 1978 - C.S. file 60/11-8

Found - 18" now 20" D.Fir, is uprooted, orig. position
approx. bears N.49½°E., 31.5 ft. with a well
healed single blaze.
14" now 20" D.Fir bears N.39°W., 20.4 ft. with a
single well healed blaze.
Set a 1" x 36" I.P. with brass cap set at ground level in a
terraced area and marked "Douglas County Surveyor T22S R7W S
1/16 S26 S25 1978".
New BT - 13" D.Fir bears N.77½°E., 24.3 ft. I double blaze
and scribe "S 1/16 S25 CS BT".
Cor. is on a 40° SE slope, 50 ft. North of a small stream.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral
Surveyor, under Group No. 2824, surveyed May 2016/March 2018
- (DCSO records Vol. 59 Page(s) 23874-5)

The S 1/16 sec. cor. of secs. 25 and 26, established by
Haines, in 1957; and perpetuated by Douglas County Surveyor's
Office, in 1978; and is accepted as the cor.; monumented with
an iron post, 1¼" dia., firmly set, projecting 2" above
ground, with brass cap (properly) mkd.
from which the remains of the bearing trees mkd. by Haines
A root hole bears N.54°E., 33.5 ft., downhill of which is
a fir log, 25" dia., with a healed blaze.
A fir, 30" dia., bears N.39¾°W., 19.0 ft., with a healed
blaze.
and the remains of a BT mkd. by Douglas Co. Surveyor's Office
A decayed fir stump, 14" dia., bears N.79°E., 24.8 ft.,
with illegible scribe marks visible on partially opened
blaze.
and a new bearing tree
A fir, 5" dia., bears N.74½° E., 3.9 ft mkd. S1/16 S25 BT
Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at
the base right side-center & each monument established or
remonumented has a magnet deposited in a white plastic case
at the base of the stainless steel post. Alum. Angle iron
driven alongside each monument.