

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 600240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO records Vol. 4 Page(s) 1543-44)

-----  
Set a sandstone 14x10x6 ins., 9" in the ground for Qr. sec. cor., mkd. ¼ on W. face; from which  
A Cedar 48" dia., bears N.33°E., 190 lks. dist. mkd. ¼ S BT.  
No other trees within limits.  
Dug pits, 18x18x12 ins., N. and S. of post, 3 ft. dist., and raised mound of earth, 3½ ft. base, 1½ ft. high W. of cor. This cor. is on the northerly slope of spur, 100 ft. below top.

Wilford N. Haines, #239 - For: E.G. Whipple - Oct. 1957 - C.S. File 42/309 and M 1-59

-----  
Set from original BT to NE.  
22" Fir N.56°30'W., 17.9 ft.  
Set 1" x 1" x 36" Iron rod with brass cap inscribed "Wilford N. Haines #239 Survey Point".

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2824, surveyed May 2016/March 2018 - (DCSO records Vol. 59 Page(s) 23875)

-----  
The ¼ sec. cor. of secs. 25 and 26, perpetuated by Haines, in 1957 monumented with a "T" shaped iron rod, 3/4" dia., firmly set, projecting 4" above ground, with brass washer mkd WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE., with a tack in center,  
from which an original bearing tree  
A cedar, 54" dia., bears N.33°E., 125.4 ft., with a healed blaze.  
and a bearing tree mkd. by Haines  
A fir, 34" dia., bears N.56°W., 17.1 ft., with a healed blaze.  
At the corner point  
Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, directly over the iron rod, 36" long, with brass cap mkd  
T 22 S R 7 W  
¼  
S 26 | S 25  
2016