

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 4 Page(s) 1532)

Set 1/4 sec. post, from which
A Fir 18" dia., bears N.35°E., 35 lks. dist.
A Cedar 8" dia., bears S.55°W., 6 lks. dist.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy & C. Putnam, crew - May/June 1962 - C.S. File 52/14-108

Found - Haines T Iron. (unrecorded)
I.Cedar now 14", S.55°W., 4.0 ft., showed very good scars. Cut open lower scar and found good scribing "B", rings show tree has grown very slowly, scribing is old enough for original. I reblaze and scribe this tree "1/4 S23 CS BT".
No trace found of orig. NE BT.
New BT - 5" D.Fir N.32°E., 17.7 ft. mkd. 1/4 S24 CS BT.
Corner lies on steep East slope. Old scribing faces SE instead of NE.

BLM resurvey by Wayne L. Rogers and Lance J. Bishop, Cadastral Surveyors, under Group #1160, surveyed April/July 1984 - (DCSO records Vol. 47 Page(s) 18082)

The 1/4 sec. cor., perpetuated and recorded by Haines in 1957, further perpetuated and recorded by Godfrey in 1962, monumented with a 3" T shaped iron rod, firmly set, projecting 12" above ground, with brass disc mkd. Wilford N Haines 239 Survey Point Drain Oregon, from which the original bearing tree:

A Cedar 16" dia., bears S.55°W., 6 lks. dist. with healed blaze.
and a bearing tree mkd. by Godfrey:
A Fir 7" dia., bears N.32°E., 27 lks. dist. with healed blaze.

At the corner point
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, directly over iron rod with brass cap mkd: T 22 S R 7 W

1/4
S 23 | S 24
1984

Fd. OK, March 1990, C.S. File 63/104-33
Fd. OK, Jun. 1995, K. Hoffine, C.S. File 65/1-5