

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 4 Page(s) 1517)

Set post cor. to secs. 13, 14, 23 and 24, from which

- A Fir 30" dia., bears N.48°E., 14 lks. dist.
- A Fir 8" dia., bears S.20°E., 41 lks. dist.
- A Fir 8" dia., bears S.10°W., 10 lks. dist.
- A Maple 4" dia., bears N.54°W., 41 lks. dist.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy & C Putnam, crew - May/June 1962 - C.S. File 52/14-107

Found - Unrecorded Haines T Iron at corner.
Fir now 60", N.48°E., 9.2 ft. to center, old bark scribing visible "S T S" and portions of other letters or numbers, rescribed in bark by Haines, T22S R7W S13 33 BT.
No trace of other orig. BTs.
16" D.Fir scribed by Haines bears S.75°W., 18.0 ft., scribe pitched over.

New BTs -13" D.Fir N.78°W., 24.1 ft. mkd. T22S R7W S14 CSBT.
20" D.Fir S.15°E., 12.5 ft. mkd. T22S R7W S24 CSBT.

Fd. OK, May 1990, C.S. File 63/127-6
Fd. OK, April 1993, K. Hoffine, M 117-4

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2824, surveyed May 2016/March 2018 - (DCSO records Vol. 59 Page(s) 23881)

The cor. of secs. 13, 14, 23, and 24, perpetuated by Haines, date unknown, and further perpetuated by Godfrey, in 1962, monumented with a "T" shaped iron rod, 3/4" dia., firmly set, projecting 2" above ground, with brass washer mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE., with a tack in center, from which the remains of an original bearing tree

- A fir, 66" dia., bears N.48°E., 9.2 ft., with scribe marks T22S R7W S13 363 BT, reported by Godfrey to have been rescribed on the bark by Haines.

and a bearing tree mkd. by Haines

- A fir, 23" dia., bears S.74¼°W., 17.9 ft., with a healed blaze.

and the bearing trees mkd. by Godfrey

- A fir, 24" dia., bears S.17¾°E., 12.1 ft., with a healed blaze.
- A fir, 15" dia., bears N.78¾°W., 23.6 ft., with a healed blaze.

Continued next page

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

At the corner point
Set a stainless steel post, 28" long, 2½" dia., 24" in the
ground, directly over the iron rod, 34" long, with brass cap
mkd

T 22 S R7W	
S 14	S 13
S 23	S 24
2016	