

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 4 Pg 1515)

Set post cor. to secs. 11, 12, 13 and 14, from which
A Fir 18" dia., bears N.80°E., 32 lks. dist.
A Fir 14" dia., bears S.60°E., 25 lks. dist.
A Maple 6" dia., bears S.50°W., 18 lks. dist.
A Fir 20" dia., bears N.80°W., 42 lks. dist.

Wilford N. Haines - For: Chester Sweringen and Harold Woolley 1956 - C.S. File 51/282 and M 3-22

This corner was set from local physical objects called for in the original field notes. The old Scottsburg trail is 5.0 chs. (330 ft) East, 1.50 chs. (99.0 ft.) South. Elk Creek is 1.75 chs. (115.5 ft.) North.
Set an angle iron with brass cap at corner point inscribed "Survey Point-Wilford N. Haines #239", from which
24" Alder S.70°W., 11.0 ft.
12" Fir S.31°W., 30.9 ft.
8" Fir S.25°E., 23.8 ft.
12" W.Fir N.74°E., 22.2 ft.

Fd. OK, April 1993, K. Hoffine, M 117-4

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2824, surveyed May 2016/March 2018 - (DCSO records Vol. 59 Page(s) 23883-4)

The cor. of secs. 11, 12, 13, and 14, reestablished by Haines, in 1956, from topography calls in the original field notes, and is accepted as a careful and faithful reestablishment of the cor, monumented with a "T shaped iron rod, 3/4" dia., firmly set, projecting 8" above ground, with brass washer mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE., with a tack in center, from which the remains of the bearing trees mkd. by Haines
A decayed fir stump, 24" dia., bears N.72½°E., 22.2 ft., with no marks visible.
A decayed fir snag, 14" dia., bears S.27¼°E., 23.4 ft., with a healed blaze.

At the corner point
Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, directly over the iron rod 36" long, with brass cap mkd

T 22 S R 7 W
S11 | S12
S14 | S13
2016

Continued next page

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

from which new bearing trees
A fir, 9" dia., bears N.68½°E., 48.5 ft., mkd. T22S R7W S12 BT.
A fir, 11" dia., bears S.54°E., 14.9 ft., mkd. T22S R7W S13 BT.
A fir, 7" dia., bears S.23°W., 16.3 ft., mkd. T22S R7W S14 BT.
An alder, 28" dia., bears N.25°W., 31.2 ft., mkd. T22S R7W S11 BT.
From this cor., W., 265 ft., to Elk Creek, 40 ft. wide, course S.50°W.
Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.