

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 4 Page(s) 1515)

Set ¼ sec. post, from which
A Fir 30" dia., bears N.55°E., 29 lks. dist.
A Fir 10" dia., bears N.48°W., 14 lks. dist.

Wilford N. Haines - For: Chester Sweringen and Harold Woolley
1956 - M 3-22

Corner located by proportional measurement.
Set an angle iron with brass cap at corner point inscribed
"Survey point-Wilford N. Haines #239"., from which scribed:
30" Fir N.52°E., 47.7 ft.
X on rock 4 ft. x 4 ft. x 5 ft., S.87°W., 15.5 ft.
X on rock 6 ft. x 6 ft. x 6 ft., N.52°E., 5.1 ft.

Ken Hoffine, LS # 2291 - For: Lone Rock Timber Co. - 3/94 -
M 119-23

Found - Haines T-Iron in good condition.
30" Douglas Fir stump bears N.52°E., 47.7', bark
scribed & BLM tag.
4'x4'x5' rock with chopped "X" on face bears
S.87°W., 15.5 ft, I paint.
6'x6'x6' rock with chopped "X" on face bears
N.52°E., 5.1 ft. I paint.
New BT- 7" Douglas Fir, bears S.24°E., 8.5 ft. I tag tree.
Corner lies on extremely steep rock West slope.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral
Surveyor, under Group No. 2824, surveyed May 2016/March 2018
- (DCSO records Vol. 59 Page(s) 23885)

The ¼ sec. cor of secs. 11 and 12, reestablished by Haines,
in 1956. and perpetuated by Hoffine, in 1994; and is accepted
as a careful and faithful reestablishment of the cor.,
monumented with a 'T' shaped iron rod, 3/4" dia., firmly set,
projecting 13" above ground, with brass washer mkd. WILFORD
N. HAINES 239 SURVEY POINT DRAIN, ORE. with a tack in center,
from which the remains of the accessories mkd by Haines
A burnt, sawed fir stump, 32" dia., bears N.52¼°E., 47.5
ft., with scribe marks ¼ BT visible on bark.
A boulder, 4 x 4 ft., projecting 4 ft. above ground, bears
S.82°W., 14.2 ft., mkd. with a cross (X) chiseled on
the east face.
continued next page

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A boulder, 6 x 6 ft., projecting 6 ft. above ground bears S.45¼°W., 5.0 ft., mkd. with a cross (X) chiseled on the NE face.
and a bearing tree mkd. by Hoffine
A fir, 9" dia., bears S.26½°E., 8.4 ft., with a healed blaze.
At the corner point
Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, directly over the iron rod 40" long, with brass cap mkd
T 22 S R 7 W
¼
S 11 | S 12
2016