

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 600700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 2; 35 & 36, T21-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 631)

Set post corner of secs. 1, 2, 35 and 36, from which
A Fir 12" dia., bears N.45°W., 16 lks. dist.
A Fir 12" dia., bears S.36°W., 32 lks. dist.
A Maple 8" dia., bears S.40°E., 14 lks. dist.
A Maple 6" dia., bears N.34°E., 42 lks. dist.

Original, Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO Records, Volume 2 Page 634)

At the cor. to secs. 1, 2, 35 and 36, I found but one witness tree standing. Reestablished the corner by setting a post, 6" dia., 4 ft. long, with marked stone, 12" in ground, mkd. T21S S36 on NE.; R7W S1 on SE.; T22S S2 on SW.; and S35 on NW. face, with one notch on E. and 5 on W. edges; from which
Fir 24" dia., bears S.36°W., 32 lks. dist., mkd. T22S R7W S2 BT.
Fir 24" dia., bears N.49°W., 72 lks. dist., mkd. T21S R7W S35 BT.
Alder 8" dia., bears N.85°E., 28 lks. dist. mkd. T21S R7W S36 BT.
Maple 12" dia., bears S.15°E., 20 lks. dist. mkd. T22S R7W S1 BT.

Wilford N. Haines - March 1957 - M 4-52

Found original corner.
Set a 1" x 36" Iron rod at corner point with brass cap inscribed "Wilford N. Haines, Survey Point, #239"

Wilford N. Haines - Feb. 17, 1960 - C.S. File 51/67-2

Found - Orig. BT, Fir S.36°W., 32 lks.
Maple S.15°E., 20 lks.
Set 1" x 36" T. Iron.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy & C Putnam, crew - April/May 1962 - C.S. File 52/14-102 & C.S. File 52/14-111

Found - Haines T Iron and cap.
Fir stump now 52", S.36°W., 20.1 ft. (instead of 21.1 ft.) scribing visible on old face, stump good condition.
24" Maple S.15°E., 13.2 ft. scribing visible on old face.
No other bearing trees found. (Cont. Next Page)

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 600700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 2; 35 & 36, T21-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs -28" R.Cedar N.34°W., 52.9 ft. mkd. T21S R7W S35 CS BT, one blaze.
24" D.Fir N.62°E., 53.0 ft. mkd. T21S R7W S36 CS BT, bark scribe.
No other trees available in section 2.

BLM resurvey by James E. Jelley, under Group #1081, surveyed Sept/Oct. 1981 (DCSO records Vol. 45 Page(s) 17231-32)

The Sec. cor., perpetuated and recorded by Haines in 1960, and perpetuated and recorded by Godfrey in 1962, monumented with a 3/4" "T" shaped iron rod, firmly set, projecting 2" above the ground, with an alum. washer mkd. "Wilford N. Haines Survey Point 239", from which the remains of an original bearing tree

A sawed Fir stump 52" dia., bears S.36°W., 32 lks. with fragmentary scribe marks visible on opened blaze.
and a bearing tree mkd. by Wheeler

A Maple 23" dia., bears S.15°E., 22 lks., with fragmentary scribe marks visible on decayed blaze. (Rec. 20 lks.)
and bearing trees mkd. by Godfrey

A Fir 30" dia., bears N.62°E., 80 lks. dist. with fragmentary scribe marks visible on bark blaze.

A Cedar 28" dia. bears N.34½°W., 79½ lks. with fragmentary scribe marks visible on partially healed blaze.
and a tree not of known record

A Fir 44" dia., bears N.44°W., 71 lks. dist., with fragmentary scribe marks visible on bark blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 21 S R 7 W
<u>S 35 S 36</u>
S 2 S 1
T 22 S R 7 W
1981

from which new bearing trees

A Hemlock 8" dia., bears S.43°E., 95½ lks. dist. mkd. T22S R7W S1 BT.

A Grand Fir 12" dia., bears S.86°W., 29½ lks. dist. mkd. T22S R7W S2 BT.

Deposit the T shaped iron rod alongside the iron post.

Cor Fd & used in BLM resurvey by Boyd Peterson, Cad Surveyor, surveyed Sept/Dec. 1986 (DCSO recs Vol. 48 Pg 18307)

Fd. BC & 6 BTs Set 6' post 1' W, H Christensen, Jan 2005, M147-9