

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 607300

PRIMARY CORNER DESCRIPTION C C for Secs. 25 and 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO records Vol. 4 Page(s) 1544)

At a point 7.10 chs. East of the cor. for secs. 23 and 26, I set a sandstone, 14x12x10 ins., 9" in the ground, for a closing corner of secs. 25 and 26, mkd. C C on the S., with 1 groove on E., and 2 grooves on S. faces; from which
 A Fir 8" dia., bears S.59°E., 50 lks. dist. mkd. T22S R7W S25 BT.
 A Fir 50" dia., bears S.85°W., 40 lks. dist. mkd. T22S R7W S26 BT.
This cor. is on a S. slope, 75 ft. above creek.

Wilford N. Haines, #239 - For: E.G. Whipple - Oct. 1957 - C.S. File 42/309 and M 1-59

Set from original BTs.
Set 1" x 1" x 36" Iron rod with brass cap inscribed "Wilford N. Haines #239 Survey Point".
True point for C C is S.02°58'E., 21.18 ft.

Fd. Ok May 23, 1962 by MEG, DCSO C.S. File 52/14-105

Douglas Co. Surveyors Office - Gary L. Langlitz, Deputy - A. Vic Cangie; M. Lenora Ladig, crew - Dec. 29, 1975 - C.S. File 57/39-49

Found - 1" x 1" T Iron set by Haines in 1957 near the base of a 30" D.Fir.
 An Orig. 8" now 30" D.Fir, alive and completely healed, bears S.59°E., 33.0 ft.
 An orig. 50" now 60" D.Fir, scribing visible on previously opened blaze, bears S.85°W., 26.4 ft.
We do not set a brass cap.
New BT - An 18" D.Fir bears S.40°W., 57.9 ft. scribed "CC T22S R7W S26 CS BT" in a double blaze.

Fd. OK, 3/1990, K. Hoffine, C.S. File 63/104-35
Fd. OK, Jun. 1995, K. Hoffine, C.S. File 65/1-5

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2824, surveyed May 2016/March 2018 - (DCSO records Vol. 59 Page(s) 23876)

True point for the closing cor. of secs. 25 and 26, at intersection with the S. bdy. of sec 24

continued next page

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 607300

PRIMARY CORNER DESCRIPTION C C for Secs. 25 and 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd.

T 22 S R7W
S 24
C C
S 26 S 25
2017

from which

A fir, 19" dia., bears S.68½°E., 19.6 ft., mkd. T22S R7W S25 CC BT.

A fir, 7" dia., bears S.41¾°W., 19.8 ft., mkd. T22S R7W S26 CC BT.

From this cor. a point established by person(s) unknown bears S.59°00'25"W. 2.61 ft. and was not utilized in the course of this survey, monumented with the original closing corner, a sandstone, 14x12x10", lying loose on top of the ground, mkd CC on one face, 1 groove on an adjacent face and 2 grooves on the other face with a nail driven flush with the ground surface directly underneath the stone. The stone was removed and returned to its original location and the nail was removed from the area.

From this same cor., the original closing cor. of secs. 25 and 26, perpetuated by Haines, in 1957, further perpetuated by Douglas County Surveyor's Office, in 1975, bears N.3°03'02"W., 20.15 ft., monumented with a 'T' shaped iron rod, 3/4" dia. firmly set, projecting 12" above ground with brass washer mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN ORE., with a tack in center, from which the remains of the original bearing trees

A sawed decayed fir stump, 35" dia., bears S.59°E., 33.0 ft., with a healed blaze.

A sawed decayed fir stump, 60" dia. bears S.78¾°W., 26.4 ft., with illegible scribe marks visible on partially opened blaze. (Record, S.85°W.)

and the remains of a BT mkd. by Douglas Co. Surveyor's Office

A sawed decayed fir stump, 24" dia., bears S.40°W., 57.8 ft. with a healed double blaze.

At the original closing corner Drive the "T" shaped iron rod, flush with the ground and add the marks AM to the original stone and bury alongside the "T" shaped iron rod.