

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. sec. 24 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO records Vol 4 Pg 1543)

-----  
Set a Dogwood post, 3 ft. long, 4" sq., 24" in the ground for 1/4 sec. cor., mkd. 1/4 S on N. face, from which  
    An Alder 6" dia., bears N.59°E., 35 lks. dist. mkd. 1/4 S BT  
    A Fir 6" dia., bears S.27°W., 62 lks. dist. mkd. 1/4 S BT.  
This Qr. sec. cor. is on the NW slope of spur about 50 ft. below top.

Wilford N. Haines, #239 - For: E.G. Whipple - Oct. 1957 - C.S. File 42/309 and M 1-59

-----  
Set 1" x 1" x 36" T iron with brass cap.  
Scribed -20" Fir N.33°W., 21.8 ft.  
          12" Fir S.63°E., 73.3 ft.

DCSO by MEG 5/15/1962 - fd "T" iron & 1 BT (added 3/21/2018)  
C.S. File 52/14-15

Ken Hoffine - Wit: Gary Angiolet- For: Lone Rock Timber Co. -March 1990 - C.S. File 63/127-7

-----  
Found - Corner is a Haines T-Iron in good condition.  
        36" D.Fir bears S.63°E., 73.0 ft., bark scribed and BT tag.  
        22" D.Fir, dead decayed snag, bears N.33°W., 21.8 ft. bark scribed and BT tag.  
New BT - Put up a Lone Rock Timber location tag on a 18" Grand Fir bearing N.66°E., 12.0 ft.  
Painted faces and wrote BT on tree trunks of BTs with fluorescent orange paint.  
Corner lies approx. 75 ft. East of small clearing in young timber.

Fd. OK, Jun. 1995, K. Hoffine, C.S. File 65/1-5

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2824, surveyed May 2016/March 2018 - (DCSO records Vol. 59 Page(s) 23877-8)

-----  
The 1/4 sec. cor. of sec. 24 only, restored by Haines, date unknown; recovered and reported by Godfrey, in 1962; perpetuated by Hoffine PLS No. 2291, in 1990; and is accepted as the best available evidence of the cor. monumented with a "T" shaped iron rod 3/4" dia., firmly set, projecting 11" above ground, with brass washer mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE with a tack in center, cont.

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. sec. 24 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of the bearing trees mkd by Haines as reported by Hoffine  
A fir, 45" dia., bears S.65½°E., 73.6 ft., with scribe marks ¼ S BT visible on bark.  
A hollowed decayed fir snag, 22" dia., bears N.31°W., 21.7 ft., with a healed blaze  
and the remains of a bearing tree tagged by Hoffine  
A decayed fir snag, 14" dia., bears N.60¾°E., 11.9 ft., with no marks visible.  
At the corner point Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, directly over the iron rod 40" long with brass cap mkd  
T 22 S R 7 W  
¼ S 24  
2016  
and a new bearing tree  
A fir, 7" dia., bears N.26°W., 13.9 ft., mkd. ¼ S24 BT.  
Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.