

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 4 Pg 1531)

-----  
Set ¼ sec. post, from which  
A Cedar 30" dia., bears N.36°W., 18 lks. dist.  
A Cedar 24" dia., bears S.45°W., 10 lks. dist.

Wilford N. Haines, #239 - For: (?) Date (?) - Haines field books H-117 and H-102

-----  
An old BT, N.36°W., 11.9 ft.  
Roots of old SW BT.  
Scribed - A 16" Fir "¼ S24 BT", S.38½°W., 59.6 ft.  
A 24" Fir N.23°E., 68.3 ft. "¼ S13 BT."

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; C. Putnam - Feb. 3, 1960 - C.S. File 52/14-5

-----  
Found - Haines angle iron and cap at corner and BTs scribed by Haines 3 or 4 years ago.  
Orig. 30" now 40" Cedar, down, shows good scribing.  
Checks corner location.  
Haines BTs thus:  
22" R.Fir N.23°E., 68.3 ft.  
17" R.Fir S.37°W., 59.6 ft.

Fd. OK, March 1994, K. Hoffine, M 119-23

Ken Hoffine - For: Lone Rock Timberland - 11/2009 - M160-18

-----  
Found - Haines T-iron 0.8 ft. above ground.  
17" W.Fir bears S.78½°E., 38.1 ft. (rec. S.81°E., 38.5 ft.) visible scribing & tag.  
20" Hemlock bears N.84¼°W., 38.4 ft. no record, visible scribing & tag that reads N.81°W. 38.2 ft  
Note - T-iron bears approx. 70 ft. west of Brush Creek Rd. on flat in stand of 30 ft. tall reprod.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2824, surveyed May 2016/March 2018 - (DCSO records Vol. 59 Page(s) 23880-1)

-----  
The ¼ sec. cor. of secs. 13 & 24, perpetuated by Haines, from original evidence no longer in existence; further perpetuated by Hoffine, in 1994, and perpetuated by person(s) unknown as reported by Hoffine in 2009; monumented with a "T" shaped iron rod, 3/4" dia, firmly set, projecting 7" above ground, with brass washer mkd. Continued next page

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 24

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE., with a tack in center,

from which the remains of the bearing trees mkd. by Haines  
A sawed decayed fir stump, 31" dia., bears N.22 $\frac{3}{4}$ °E., 68.2 ft., with a healed blaze.

A sawed decayed fir stump, 30" dia., bears S.38 $\frac{1}{4}$ °W., 59.7 ft., with a healed blaze.

and a bearing tree mkd. by Hoffine in 1994

A fir, 19" dia., bears S.79 $\frac{1}{4}$ °E., 38.0 ft., with a healed blaze.

and a bearing tree mkd. by person(s) unknown, reported by Hoffine in 2009

A hemlock, 20" dia., bears N.84 $\frac{1}{2}$ °W. 38.5 ft., with scribe marks  $\frac{1}{4}$  S13 BT visible on partially healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2 $\frac{1}{2}$ " dia., 24" in the ground, directly over the iron rod 36" long with brass cap mkd

T 22 S R 7 W

$\frac{1}{4}$   $\frac{S 13}{S 24}$

2016