

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 12 and 13

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 4 Page(s) 1514-15)

Set ¼ sec. post, from which
A Fir 16" dia., bears N.28°E., 61 lks. dist.
A Dogwood 8" dia., bears S.50°E., 47 lks. dist.

Wilford N. Haines - For: Chester Sweringen and Harold Woolley
1956 - M 3-22

Corner located by proportional measurement.
Set an angle iron with brass cap at corner point inscribed
"Survey Point Wilford N. Haines #239", from which scribed:
12" Fir S.62°W., 6.5 ft.
8" Fir N.26°E., 7.0 ft.

Fd. OK, March 1994, Ken Hoffine, M 119-23
FD. OK by D. Edwards, Oct. 1999 - CS 65/25-8

Douglas Co. Surveyors Office - Stephen J. Flause - Mike Koch
- Feb. 8, 2013 - C.S. File 67/38-8

Found - A 1" dia., brass washer (properly mkd) on a 1"x1"
"T" iron firmly and plumbly set, protruding 10"
above ground.
No stumps or trees in area large enough or old
enough to be OBTs
A 12" now a 24" dia., 4½ ft. tall D.Fir stump with
a fully healed single blaze; bears S.62°W., 6.5
ft. (as per rec.) 1956
An 8" fir now a 12" dia., 5½ ft. tall D.Fir stump
with a fully healed single blaze; bears N.29°E.,
7.0 ft. (rec. N.26°E., 7.0 ft) 1956
New - Proportioned in 1956 monument is stable and in good
condition; we leave as found.
A 5" dia., G.Fir scribed "X" "CSBT" on a high-low;
bears N.73°E., 10.1' ft.
A 7" dia., D.Fir scribed "X" "CSBT" on a double
blaze; bears South 6.1 ft.
A 6" dia., D.Fir scribed "¼S12CS" "BT" on a double
blaze; bears West, 24.4 ft.
No suitable trees in NW quadrant.
Note - Monument is on gentle north slope in young reprod
fir forest. Monument is just north and west from
NW corner of an older fire regrowth fir forest.

continued next page

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 12 and 13

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2824, surveyed May 2016/March 2018 - (DCSO records Vol. 59 Page(s) 23884-5)

The 1/4 sec. cor. of secs. 12 and 13, reestablished by Haines, in 1956 by proportionate measurement, perpetuated by the Douglas Co. Surveyor's Office in 2013, and is accepted as a careful and faithful reestablishment of the cor., monumented with a "T" shaped iron rod, 3/4" dia., 36" long, firmly set, projecting 9" above ground, with brass washer mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE., with a tack in center, from which the remains of the bearing trees mkd. by Haines

A sawed decayed fir stump, 12" dia., bears N.31°E., 7.0 ft. with a healed blaze.

A sawed decayed fir stump, 26" dia., bears S.63 3/4°W., 5.5 ft., with a healed blaze.

and the bearing trees mkd. by Douglas Co. Surveyor's Office

A fir, 7" dia., bears N.73 1/2°E. 10.0 ft., with scribe marks S BT visible on partially healed double blaze.

A fir, 9" dia., bears S.0 3/4°W., 6.0 ft., with illegible scribe marks visible on partially healed double blaze.

A fir, 8" dia., bears S.89 3/4°W., 24.6 ft. with scribe marks 1/4 S12 CS BT visible on partially healed double blaze.

At the corner point

Set a stainless steel post, 28" long, 2 1/2" dia., 26" in the ground, directly over the iron rod with brass cap mkd.

T 22 S R 7 W

1/4 S 12
S 13
2016