

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 640600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 12

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 4 Page(s) 1516)

-----  
Set ¼ sec. post, from which  
A Chinquapin 8" dia., bears N.70°W., 35 lks.  
A Dogwood 8" dia., bears S.85°E., 18 lks.

Wilford N. Haines -For: Chester Sweringen and Harold Woolley  
1956 - M 3-22

-----  
Corner located by proportional measurement.  
Set an angle iron with brass cap at corner point inscribed "Survey Point-Wilford N. Haines #239", from which  
52" Fir S.88°W., 23.6 ft.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2824, surveyed May 2016/March 2018 - (DCSO records Vol. 59 Page(s) 23887)

-----  
Point for the ¼ sec. cor. of secs. 1 and 12, at proportionate dist., there is no remaining evidence of the original cor. Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd.

T 22 S R 7 W  
¼  $\frac{S 1}{S 12}$   
2016

from which  
A fir, 10" dia., bears S.63°W., 44.9 ft. mkd. ¼ S12 BT.  
A fir, 9" dia., bears N.26¼°W., 7.9 ft., mkd. ¼ S1 BT.  
Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.  
Note: No evidence of the local ¼ sec. cor. of secs. 1 and 12, reestablished by Haines PLS No. 239, in 1956, was found.