

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 640700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 1; & 36 of T21-7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 631)

-----  
Set qr. sec. post; from which  
A Fir 36" dia., bears N.38°E., 29 lks. dist.  
A Fir 36" dia., bears S.30°W., 40 lks. dist.

BLM resurvey, by Boyd W. Peterson, under special instructions dated August 18, 1986, under Group #1346, Surveyed Sept./Dec. 1986 (DCSO records Vol. 48 Page(s) 18306-07)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an stainless steel post, 28" long, 2 1/2" dia., 25" in the ground, with brass cap mkd:  
T 21 S R 7 W  
¼ S 36  
S 1  
S 22 S  
1986

from which  
A Fir 17" dia., bears S.31½°W., 10 lks. dist. mkd. ¼ S1 BT  
A Fir 21" dia., bears N.14½°W., 15 lks. dist. mkd. ¼ S36 BT.  
Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

Fd OK by D.Baker, 12/91, M 114-26