

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec. cor. 25 & 36 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1431)

Set post cor. of secs. 25, 30, 31 and 36, from which
A Fir 14" dia., bears N.15°W., 23 lks. dist.
A Fir 8" dia., bears N.40°E., 14 lks. dist.
A Maple 10" dia., bears S.85°W., 18 lks. dist.
A Laurel 14" dia., bears S.52°E., 71 lks. dist.

GL0 survey by Carl S. Nicklin, Deputy Surveyor, under Special Instructions dated Oct. 27, 1897 (DCSO records Vol. 4 Page(s) 1463 and 1537-38)

(On Page 1463, from cor. estab. for 30 & 31 only, "the old cor. of secs. 25, 30, 31 and 36, bears S.0°15'W., about 260 lks. dist.; post decayed. I destroy old cor."

(On pages 1537-38), At point of intersection, I Set a Madrona post, 3 ft. long, 4" sq., 24" in the ground, for closing cor. of secs. 25 and 36, mkd. C C T22S R7W on W.; S25 on N.; and S36 on S. faces; with 1 groove on the S. and 5 grooves on N. faces; from which

A Fir 24" dia., bears S.83½°W., 142 lks. dist. mkd. T22S R7W S36 BT.

A Fir 20" dia., bears N.71°W., 141 lks. dist. mkd. T22S R7W S25 BT.

The closing cor. is on the Southerly slope of ridge 50 ft. below top.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; C. Putnam - Feb. 3, 1960 - C.S. File 52/14-3

Found - Orig. 20" now 31" Fir N.71°W., 93.1 ft. shows good scribing on old face.

Orig. SW BT not found.

Set Brass cap at cor. mkd: County Surveyors Office

T 22 S
R7W $\frac{S25}{S36}$ | R6W
1960

Rescribe - 31" R.Fir N.71°W., 93.1 ft. CC S25 R7W T22S.
No trees near to SW.

Douglas Co. Surveyors Office - Larry E. Monrean, Deputy - T.R. Plouff, witness - Sept. 17, 1981 - C.S. File 61/27-44

Found - Brass cap on a 1" iron pipe properly mkd., firmly set, protruding 12" above ground.

(Cont. Next Page)

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec. cor. for 25 & 36 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

31" Fir (orig. 20") bears N.71°W., 93.1 ft. rescribed. The scribed "S" visible in partially healed blaze. Tree is uprooted.

New BTs -22" W.Fir scribed "T22S R7W S36 CS BT" on double blaze bears S.37°W., 22.2 ft.

16" D.Fir scribed X B0 CS BT on double blaze bears S.30½°E., 38.0 ft.

16" D.Fir scribed "T22S R7W S25" on double blaze bears N.25½°W., 52.8 ft.

Fd. OK, Feb. 1994, K. Hoffine, C.S. File 63/154-5
Fd. OK, Feb. 1995, K. Hoffine, C.S. File 63/161-27

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2824, surveyed May 2016/March 2018 - (DCSO records Vol. 59 Page(s) 23873)

The closing cor. of secs. 25 and 36, on the E. bdy. of the Tp., perpetuated by Byron, in 1960; further perpetuated by Monrean, in 1981, monumented with an iron post, 1¼" dia., firmly set, projecting 15" above ground, with brass cap (properly) mkd.
from which the remains of an original bearing tree
A root hole bears N.71°W., 93.1 ft., alongside of which is a decayed fir log, 25" dia., with no marks visible.
and the remains of the bearing trees mkd. by Monrean
A fir, 41" dia., bears S.29¼°E., 38.2 ft., with a healed blaze.
A sawed decayed fir stump, 34" dia., bears S.35¾°W., 22.3 ft., with illegible scribe marks visible on partially opened blaze.
A fir, 32" dia., bears N.26°W., 52.7 ft., with a healed double blaze.
and a new bearing tree
A cedar, 9" dia., bears S.77¼°W., 34.7 ft., mkd. T22S R7W S36 BT.
Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.
NAD 1983 (2011)
Latitude: 43° 37' 12.93" N. Longitude: 123° 28' 02.20" W.