

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Special Instructions dated Oct. 27, 1897 (DCSO records Vol. 4 Page(s) 1462)

Set a Madrona post, 3 ft. long, 4' sq., 24" in the ground for cor. of secs. 30 and 31, T22S R6W, mkd. T22S S30 on NE.; and R6W S31 on SE. faces, with 5 notches on N. and 1 notch on S. edges, from which

A Cedar 36" dia., bears N.83°E., 237 lks. dist. mkd. T22S R6W S30 BT.

A Fir 48" dia., bears S.30°E., 141 lks. dist. mkd. T22S R6W S31 BT.

This cor. is on the S. slope of spur about 25 ft. below top.

Wilford N. Haines - For: Whipple Mill - 1955 - M 2-13

Found - Old I.Cedar BT.

Set angle iron with brass cap inscribed Survey Point-Wilford N. Haines 239.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; Clete Putnam - Feb. 3, 1960 - C.S. File 52/14-2

Found - Orig. 36" now 55" Cedar N.83°E., 156.4 ft. I re-open and find good reverse scribing "S".

Also find shell of stump that checks bearing and dist. for orig. SE BT.

Set Brass cap at cor. mkd: County Surveyors Office

T 22 S
R7W | S 30 R6W
 | S 31
 1960

New BTs -55" Cedar S.76°E., 128.0 ft. scribed S31 T22S R6W CS BT.

Rescribed now 55" Cedar N.83°E., 158.0 ft. "S30 T22S R6W CS BT"

Haines angle iron and old sq. stake bears S.5°E., 6.3 ft.

Douglas Co. Surveyors Office - Larry E. Monrean, Deputy - T.R. Plouff, crew - Sept. 21, 1981 - C.S. File 61/27-47

Found - Brass cap on a 1" iron pipe, properly mkd., firmly set, and protruding 8" above ground.

Orig. 36" Cedar rescribed by Byron, "T22S R6W S30 BT" legible. This tree now a badly decayed stump with debris piled against it. Stump bears N.83°E., 155.7 ft. to approx. center. (Rec.

N.83°E., 156.4 ft.)

(Cont. Next Page)

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 700204

PRIMARY CORNER DESCRIPTION Sec. cor. for 30 & 31 only, T22-6

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

The orig. 48" Fir, now a decayed stump with no scribing or blaze remaining, bears S.29°E., 96.1 ft. to approx. center (Rec. S.30°E., 93.1 ft.)
 Snag (orig. 55" Cedar) scribed "T22S R6W CS BT" bears S.76°E., 128.0 ft. (scribe visible)
 New BTs -12" D.Fir scribed "T22S R6W S31 CS BT" on double blaze, bears S.28°E., 89.6 ft.
 14" D.Fir scribed "T22S R6W S30 CS BT" on double blaze, bears N.88½°E., 46.5 ft.
 16" D.Fir scribed "T22S R5W S30 CS BT" on double blaze, bears N.71°E., 42.8 ft.
 Haines T Iron bears S.8½°E., 6.25 ft.

Fd. OK, Feb. 1994, K. Hoffine, C.S. File 63/154-5

Fd. OK, Jan. 1996, K. Hoffine, C.S. File 65/2-3
 Note - Corner lies approximately 1 chain north of young fir timber and in planted pine stand. Corner is also approximately 55 feet south of main ridge.