

PRIMARY CORNER DESCRIPTION Sec. cor. for 24 & 25 only

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GL0 survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1431)

- 
- Set post cor. of secs. 19, 24, 25 and 30, from which
- A Fir 10" dia., bears S.60°W., 45 lks. dist.
  - A Fir 36" dia., bears S.18°E., 69 lks. dist.
  - A Fir 12" dia., bears N.26°W., 38 lks. dist.
  - A Hemlock 14" dia., bears N.45°E., 72 lks. dist.

GL0 survey by Carl S. Nicklin, Deputy Surveyor, under Special Instructions dated Oct. 27, 1897 (DCSO records Vol. 4 Page(s) 1461 and 1542)

-----

(On page 1461): "The old cor. of secs. 19, 30, 24 and 25, of which the only remaining indication is one bearing tree - bears S., about 150 lks. dist" (from sec. cor. established for 19 and 30 only, T22-6)

(On page 1542): At point of intersection, I  
Set a sandstone 12x8x8 ins. 8" in the ground, for closing cor. of secs. 24 and 25, mkd. C C on W., with 2 grooves on N. faces; from which

- A Maple 5" dia., bears S.68°W., 46 lks mkd T22S R7W S25 BT
- A Cedar 14" dia., bears N.8°W., 57 lks mkd T22S R7W S24 BT

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy & Clete Putnam, crew - Aug. 1961 - C.S. File 49/143-66

-----

Found - Haines T Iron and cap. (No record source found)  
Maple tree, now 10", S.68°W., 31.0 ft., previously opened, old scribing visible in opened face.

New BTs -28" R.Cedar N.8°E., 26.3 ft. mkd. "CC S24 S25 CS BT"  
12" Maple S.39°E., 13.5 ft. mkd. "CC S24 S25 CS BT"

Fd. OK, July 1990, C.S. File 63/104-36  
Fd. OK, Feb. 1994, K. Hoffine, C.S. File 63/154-5  
Fd. OK, Jun. 1995, K. Hoffine, C.S. File 65/1-5

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2824, surveyed May 2016/March 2018 - (DCSO records Vol. 59 Page(s) 23879)

-----

The closing cor. of secs. 24 and 25, on the E. bdy. of the Tp., perpetuated by Haines, date unknown, recorded and further perpetuated by Godfrey in August 1961, monumented with a "T" shaped iron rod, 3/4" dia., firmly set, projecting 9" above ground, with brass washer mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE., with a tack in center,

continued next page

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec. cor. for 24 & 25 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

from which an original bearing tree  
A maple, 18" dia., bears S.77°W., 30.4 ft., with a healed blaze. (Record, S.68°W.)  
and the bearing trees mkd. by Godfrey  
A cedar, 27" dia., bears N.9½°E., 26.2 ft. with illegible scribe marks visible on partially opened blaze.  
A maple, 14" dia., bears S.42°E., 12.6 ft., with a healed double blaze.

At the corner point  
Set a stainless steel post, 28" long, 2½" dia., 4" in the ground, supported in a mound of stone, 3 ft. base, to the top, with brass cap mkd.

T 22 S  
R7W R6W  
S 24 |  
S 25 | S 30  
2016

from which a new bearing tree  
A cedar, 11" dia. bears N.21½°W., 19.0 ft. mkd. T22S R7W  
CC S24 BT.

Bury the iron rod, 30" long, alongside the stainless steel post.

Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.