

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 13; & 18, T22-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1432)

Set ¼ sec. post, from which
A Fir 12" dia., bears N.85°W., 27 lks. dist.
A Maple 10" dia., bears S.55°E., 10 lks. dist.

Wilford N. Haines - For: Chester Swerigen and Harold Woolley 1956 - M 3-22 (and H-102)

Found - Orig. Fir BT.
Maple is dead and down.
Set an angle iron with brass cap inscribed Survey Point-Wilford N. Haines #239
(wording from H-102: 12" Fir, N.08°30'E., 26.3 ft.
Rescribed (bark) original BT to West, 51" Fir.)

Fd. OK, March 1994, K. Hoffine, M 119-23

Ken Hoffine - for Lone Rock Timber Co. - Dec. 1994 - M 121 - 43

Found - Haines T-iron
24" D.Fir, bears N.8°E. 24.5 ft., no face, 3 B.T. tags
52" D.Fir, bears S.10°W. 25 ft., no face, LRT location tag.
Orig. 12" D.Fir, is a 55" rotten stump, bears N.85°W. 17.8 ft., old face visible, no scribing.
Orig. 10" Maple, is a 21" wind fall, bears S.55°E. 6.6 ft., no visible scribing.
Corner lies on a 50% southwest slope. BLM clearcut to the Northwest.

Douglas Co. Surveyors Office - Randall Smith, Deputy - Jan. 20, 1995 - C.S. file 64/58-3

Found - Haines T-Iron with 1" dia. washer on top mkd. "Wilford N. Haines 239-Survey Point Drain Ore", protrudes 10" above ground.
12" now 55" dia. 4 ft. high rotted D.Fir stump bears N.85°W., 17.8 ft. (agrees w/rec) O.B.T. We open and find scribing "BT"
10" now 21" dia. down and rotted Maple, bears S.55°E., 6.6 ft. (agrees w/rec) O.B.T. We open, no scribing found.

(Cont. Next Page)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

24" dia. D.Fir, no blazes, bears N.8°E., 23.7ft.
(Rec. N.8°E., 24.5 ft.) We double blaze and
scribe "¼ S13 CS BT"
52" dia. D.Fir, no blazes, bears S.10°W., 25.0 ft.
(agrees w/rec.) We bark scribed "¼ S18 CS BT"
Haines T-Iron is referenced and removed. At referenced
position, a 2½" dia. DCSO brass cap on a 1 3/8" x 32" long
iron pipe is SET. BC/IP protrudes 9" above ground. 24" long
Haines T-Iron is set along South edge of BC/IP, protrudes 4"
above ground. BC is mkd: Douglas County Surveyors
T 22 S
R R
7 S13|S18 6
W 1/4 W
1995
Office
New BTs -12" dia. Maple double blazed and scribed "¼ S13 CS
BT", bears N.40½°W., 15.8 ft.
18" dia. D.Fir double blazed and scribed "¼ S18 CS
BT" bears S.56°E., 42.4 ft.

Ken Hoffine - For: Lone Rock Timberland Co - 11/2009 - M160-18

Found - 1995 Douglas Co. brass cap at Haines T-iron position
for quarter corner.
55" rotted D.Fir stump bears N.85°W., 17.8 ft. as
per record.
24" tall D.Fir stump bears N.8°E., 23.7 ft. as per
record.
52" D.Fir bears S.10°W., 25.0 ft. as per record.
14" Maple bears N.40½°W., 15.8 ft. as per record.
18" tall D.Fir stump bears S.56°E., 42.4 ft. as per
record.
Corner lies on 50% Southwest slope recent clear-cut to east
of corner.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral
Surveyor, under Group No. 2824, surveyed May 2016/March 2018
- (DCSO records Vol. 59 Page(s) 23867-8)

The ¼ sec. cor of secs. 13 and 18, perpetuated by Haines, in
1956 and under FB H-102; and further perpetuated by Smith, in
1995; monumented with an iron post, 1¼" dia. firmly set,
projecting 10" above ground (alongside of which is a "T'
shaped iron rod, 3/4" dia., firmly set, projecting 4" above
ground, with brass washer mkd. WILFORD N. HAINES 239 SURVEY
POINT DRAIN, ORE., with a tack in center) with brass cap
(properly) mkd. Continued next page

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 13; & 18, T22-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of the original bearing trees
A root hole bears S.55°E., 6.6 ft., alongside of which is
a decayed fallen maple trunk, size indeterminate, with
a hollowed blaze.
A decayed fir stump, 55" dia., bears N.85°W., 17.8 ft.,
with axe marks visible on bark.
and the remains of a bearing tree mkd. by Haines
A sawed decayed fir stump, 26" dia., bears N.9°E., 23.5
ft., with a healed blaze.
and the remains of the bearing trees mkd. by Smith
A sawed decayed fir stump, 20" dia., bears S.54½°E., 42.4
ft., with a healed blaze.
A fir, 56" dia., bears S.11¾°W., 24.7 ft., with scribe
marks ¼ S13 BT visible on bark.
A maple, 18" dia., bears N.41½°W., 16.0 ft., with a healed
blaze.