

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 12 & 13; 7 & 18, T22-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1432)

-----  
Set post cor. of secs. 7, 12, 13 and 18, from which  
A Fir 10" dia., bears N.48°E., 31 lks. dist.  
A Fir 12" dia., bears S.13°E., 49 lks. dist.  
A Maple 10" dia., bears S.17°W., 50 lks. dist.  
A Hemlock 36" dia., bears N.52°W., 37 lks. dist.

Cor. Fd. and used in GL0 survey by Byars in 1871, Contract #152 (DCSO records, Vol. 4 Page 1514)

Wilford N. Haines - For: Chester Swerigen and Harold Woolley 1956 - M 3-22

-----  
Location of corner determined by proportional measurement. Set an angle iron with brass cap inscribed: Survey Point-Wilford N. Haines #239, from which scribed:  
26" Fir S.05°E., 45.5 ft.  
26" Fir S.45°E., 51.5 ft.  
16" Fir N.13°W., 47.3 ft.  
10" Fir N.35°E., 57.7 ft.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy & C. Putnam, crew - Sept 1961 (Added 9/13/2017) - C.S. File 49/143-75

-----  
Found - "X" (6"x6"x1" deep) on rock out cropping.  
Fd. 10" Fir (scribed) N.62°E., 17.8 ft.  
Fd. 9" Fir (scribed) N.60°W., 2.6 ft.  
Fd. 12" Fir (scribed) S.58°W., 25.6 ft.  
All BTs have Haines' metal discs nailed to them.  
Note - Cor. monument & BTs fd here do not check description of cor. as recorded by Haines.

Douglas Co. Surveyors Office - Gary L. Langlitz, A. Victor Cangie & Pete L. Earle, crew - April 14, 1976 - C.S. 59/8-17

-----  
Corner Report Only  
Found - A 6" x 6" x 1" "X" chiseled into a boulder, from which  
A 14" D.Fir bears N.63°E., 18.0 ft. with Haines washer attached and with visible blaze. Blaze is facing S.20°W., not chiseled X. Tree has a BT tag that reads "S62°W 17.8 ft. Martin 8/17/56". We open and find visible "BT"

continued next page

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 12 & 13; 7 & 18, T22-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A 12" D.Fir that bears N.51°W., 2.6 ft. Tree is alive and shows good blaze. Tree has a BT tag that says "S.60°E., 2.6 ft. dist."  
A 15" D.Fir that bears S.51°W., 25.3 ft. Tree is alive and well and shows blaze. Also has Haines washer and tag that says "N.53°E., 25.6 ft."  
A 15" D.Fir bears S.41°W., 35.1 ft. Tree is alive and blaze faces East, not chiseled X.  
This corner not of record. Information given on Map number M 3-22, doesn't match condition actually at the corner.  
(Note: A letter to Mr. Haines regarding this information is in C.S. File 59/8. There was no reply.)

Donald Branch, L.S. #1137 - For: U.S. National Bank - June 16, 1986 - M 102-29  
-----  
Corner Report Only  
Found - A 4" x 4" X on 4 ft. x 6 ft. bedrock.  
18" Fir with BLM tag, Haines disc, healed blaze, bears S.53°W., 25.17 ft. (Rec. per BLM tag agrees with measured)  
12" Fir with healed blaze and BLM tag bears N.60°W., 2.10 ft.  
18" Fir with scribing visible, BLM tag, Haines disc, bears N.62°E., 18.03 ft.

Fd. OK, K. Hoffine, Dec. 1994, M 121-43  
Fd. OK, K. Hoffine, July 1996, M 125-38  
Fd. OK Oct. 1999 by D. Edwards - CS 65/25-8

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2824, surveyed May 2016/March 2018 - (DCSO records Vol. 59 Page(s) 23868-9)  
-----  
The cor. of secs. 7, 12, 13, and 18, reestablished by proportionate measurement by Haines, in 1956; recovered and accepted by Godfrey, in September, 1961; by the Douglas County Surveyor's Office, in 1976; by Branch, in 1986; and by Hoffine, in February, 1995; and is accepted as a careful and faithful reestablishment of the cor., monumented with a cross (X) chiseled in a sandstone boulder, 4 ft x 6 ft x 12" high, from which the bearing trees mkd by Haines as reported by the Douglas County Surveyor's Office  
A sawed fir stump, 25" dia., bears N.57¼°E., 18.1 ft., with a healed blaze.  
A fir, 29" dia., bears S.40°W., 34.8 ft., with a healed blaze.  
Continued next page

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 12 & 13; 7 & 18, T22-6

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

A fir, 27" dia., bears S.48¾°W., 25.0 ft., with a healed blaze.

A fir, 12" dia., bears N.45½°W., 2.6 ft., with a healed blaze.

Note. the bearing trees reported by Haines on M3-22 were so out of agreement with those found by Godfrey and the Douglas County Surveyor's Office that the Douglas County Surveyor's Office wrote to Haines in a letter dated May 25, 1976, asking him about the trees. A response to the Douglas County Surveyor's Office letter was not found.

At the corner point

Set a brass tablet, 3¼" dia., 3½" stem cemented in drill hole, flush with the top of the sandstone boulder, with top mkd.

T 22 S	
R7W	R6W
S 12	S 7
S 13	S18
2016	

from which new bearing trees

A hemlock, 4" dia., bears N.12°E., 40.7 ft., mkd. T22S R6W S7 BT.

A fir, 9" dia., bears S.10½°E., 31.6 ft., mkd. T22S R6W S18 BT.

Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.