

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 700540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 12; & 7, T22-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1433)

-----  
Set ¼ sec. post, from which  
A Fir 36" dia., bears N.38°W., 28 lks. dist.  
A Live Oak 10" dia., bears N.27°E., 17 lks. dist.

Wilford N. Haines - For: Chester Swerigen and Harold Woolley  
1956 - M 3-22

-----  
Corner location determined by proportional measurement.  
Set an angle iron with brass cap for corner, inscribed:  
Survey Point-Wilford N. Haines #239, from which scribed:  
12" Fir N.72°W., 58.8 ft.  
16" W.Fir N.45°E., 42.6 ft.

Fd. OK, Aug. 1986, D. Branch, M 102-29

Charles Guile - For: Weyerhaeuser Company - April 15, 1987 -  
C.S. File 63/54

-----  
Found - Angle iron with 1" brass disc mkd. "Wilford N.  
Haines 239 Survey Point"  
20" Fir with blaze, N.73½°W., 58.5 ft.  
24" Fir with blaze, N.45°E., 41.9 ft.  
New BTs -6" W.Fir N.46°E., 7.95 ft. to "W" nail with "X" at  
breast height.  
10" Fir S.32°E., 3.85 ft. to "W" nail.

Fd. OK, Oct. 1995 by Edwards - M122-72; CS 63/100-5  
FD. OK by D. Edwards, Oct. 1999 - CS 65/25-8

BLM dependent resurvey by Jeffrey O. Covington, Cadastral  
Surveyor, under Group No. 2824, surveyed May 2016/March 2018  
- (DCSO records Vol. 59 Page(s) 23869)

-----  
The ¼ sec. cor. of secs. 7 and 12, reestablished by Haines,  
in 1956, by proportionate measurement; and perpetuated by  
Guile, in 1987; and is accepted as a careful and faithful  
reestablishment of the cor., monumented with a "T" shaped  
iron rod, ¾" dia., firmly set, projecting 11" above ground,  
with brass washer mkd. WILFORD N. HAINES 239 SURVEY POINT  
DRAIN ORE., with a tack in center, from which the remains of  
the bearing trees mkd. by Haines  
A fir, 26" dia., bears N.45½°E., 42.3 ft., with a healed  
blaze.  
A sawed fir stump, 26" dia., bears N.73¼°W., 58.7 ft.,  
with a healed blaze. Continued next page

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 700540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 12; & 7, T22-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and the remaining bearing tree mkd. by Guile  
A fir, 10" dia bears N.44½°E., 8.2 ft., with a healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 26" in the ground, directly over the iron rod 36" long, with brass cap mkd.

T 22 S

¼

R 7 W | R 6 W

S 12 | S 7

2016

from which a new bearing tree

A fir, 11" dia., bears N.40¾°W., 8.9 ft., mkd. ¼ S12 BT. Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.