

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 700640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 1; & 6, T22-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1433)

Set ¼ sec. post, from which
A Redwood 10" dia., bears N.84°E., 21 lks. dist.
A Fir 14" dia., bears S.88°W., 22 lks. dist.

Wilford N. Haines - For: Chester Swerigen and Harold Woolley
1956 - M 3-22

Found - Orig. Fir, S.88°W., 22 lks.
Cedar stump, N.84°E., 21 lks.
Set an angle iron with brass cap inscribed: Survey Point-
Wilford N. Haines #239.
Scribed two trees:
20" D.Fir N.59°30'W., 73.2 ft.
18" W.Fir S.47°E., 165.0 ft.

Fd. OK, Dec. 1994, L. Roberts, M 121-27

BLM dependent resurvey by Jeffrey O. Covington, Cadastral
Surveyor, under Group No. 2824, surveyed May 2016/March 2018
- (DCSO records Vol. 59 Page(s) 23870-1)

The ¼ sec. cor. of secs. 1 and 6 perpetuated by Haines, in
1956 monumented with a "T" shaped iron rod, 3/4" dia., firmly
set, projecting 8" above ground, with brass washer mkd
WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE., with a tack
in center, from which the remains of an original bearing tree
A decayed fir stump, size indeterminate, bears S.88°W.,
14.5 ft., with no marks visible.
and the remains of the bearing trees mkd. by Haines
A sawed decayed fir stump, 28" dia., bears S.45¾°E., 161.3
ft., with no marks visible.
A root hole bears N.60¾°W., 71.0 ft., alongside of which
is a decayed fir snag, 24" dia., with no marks visible.
and the remains of the bearing trees mkd. by person(s)
unknown
A fir, 15" dia., bears N.87½°E., 11.1 ft., with a healed
blaze.
A root hole bears S.71½°E., 17.2 ft., alongside of which
is a decayed fir snag, 10" dia., with illegible scribe
marks visible on partially healed blaze.
A fir, 15" dia., bears S.32¾°W., 19.1 ft., with a healed
blaze.
A fir, 22" dia. bears N.33¾°W., 13.6 ft., with a healed
blaze.

Continued next page

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 700640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 1; & 6, T22-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

At the corner point
Set a stainless steel post, 28" long, 2½" dia., 26" in the
ground, directly over the iron rod 36" long, with brass cap
mkd.

T 22 S
¼
R 7 W | R 6 W
S 1 | S 6
2016