

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 041030

PRIMARY CORNER DESCRIPTION NW Cor. Wm. N. Wells DLC #41

Alias 042010 Description NE Cor. Edward Griffin DLC #42
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Surveys of Donation Land Claims by - Dennis Hathorn, Deputy,
dated Sept. 1856

At the NW cor. on left bank of Umpqua River in Sec. 23, Set
post, from which

A Maple 18" dia., bears S.65°E., 67 lks.

An Ash 24" dia., bears N.25°E., 50 lks.

Ben B. Irving, Co. Surveyor - Milo Godfrey, witness - March
1945 - M 10-72

All evidences of this corner having been destroyed, a 1/2" x
48" tie rod was set 46" in the ground for the corner, from
which

A W.Oak 6" dia., bears N.76°E., 19 ft.

An Ash 6" dia., bears N.23°W., 27.6 ft.

The location of this corner was determined by computation
from the SE corner of DLC #42 and the Meander corner on the
left bank of the Umpqua River between secs. 22 and 23. From
such computations, these positions were determined and the
one which most nearly satisfied local conditions was used.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike
Stone & Wm. Stoffel, crew - Oct. 1964 - C.S. File 52/14-69

Found - Tie rod set by Irving in 1945 with 1/2" pipe
alongside.

Ash tree, N.23°W., 27.6 ft. SE face of tree
entirely rotted away.

No trace found of NE tree.

Set Brass cap alongside tie rod and mkd:

County Surveyors Office

T 22 S R 8 W

N. E. | N. W.

DLC | DLC

42 | 41

1964

New BTs -7" Ash S.18°W., 36.0 ft. mkd. NE DLC 42 CS BT.

40" double Maple S.70°E., 23.7 ft. mkd. NW DLC 41 CS
BT.