

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 043060

PRIMARY CORNER DESCRIPTION NW Cor. Wm. Helbert DLC #43

Alias 044010 Description NE Cor. Wm. Hathaway DLC #44  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Surveys of Donation Land Claims by - Dennis Hathorn, Deputy,  
dated Sept. 1856

-----  
Set post NW cor. Claim 43, from which  
An Ash 12" dia., bears N.89°W., 87 lks.  
An Ash 10" dia., bears N.20°W., 52 lks.

Jesse W. Cole, Deputy - 1915 - Vol. 2 Page 210; Field Book 40  
Pages 29 and 30; (and "old" corner book, Page 25)

-----  
No evidence of old corner. Set a 4" x 4" x 3½ ft. post, from  
which  
A Cottonwood 16" dia., bears N.46°E., 253 lks. dist.  
A Cottonwood 16" dia., bears S.6°E., 68 lks. dist.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike  
Stone & Wm. Stoffel, crew - Sept. 1964 - C.S. File 52/14-89

-----  
Found - Old Cottonwood, down and dead, S.6°E., 44.9 ft., cut  
open and found good scribing "43" and "S".  
No trace of any other BTs.

Corner position falls on steep bank, sloping down to river,  
subject to washing during high water.

Set WITNESS CORNER 55 ft. South - Iron pipe with brass cap  
mkd: County Surveyors Office

T 22 S R 8 W  
55' N. to corner

W.C. DLC  
44 | 43  
-----  
1964

New BTs -42" W.Oak S.33½°E., 409.8 ft. mkd. W C NW DLC 43 CS  
BT.

13" W.Oak S.27½°E., 389.1 ft. mkd. NW DLC 43 CS BT.  
Corner is in remains of old N. and S. fence line.

No suitable trees available nearby.

Fd. BTs, Oct. 1986 by C. Weatherly, C.S. File 63/43

Douglas Co. Surveyors Office - Randall Smith and Stephen  
Flause, crew - April 23, 1987 - C.S. File 62/40-20

-----  
Found - 1964 Co. brass cap mkd. "County Surveyors Office  
T22S 55 ft. to cor. 44 43 W.C. R8W 1964" on a 1"  
I.D. Iron pipe, 2 ft. under surface of ground,  
plumb and firmly set. (Record stamping is "55'  
N", describing bearing and distance from W.C. to  
corner, but we find stamping is as described  
above.) (Cont. Next Page)

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 043060

PRIMARY CORNER DESCRIPTION NW Cor. Wm. Helbert DLC #43

Alias 044010 Description NE Cor. Wm. Hathaway DLC #44  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Searched for original and 1915 BTs; no evidence found.  
1964 BT, a 42" W.Oak now a 46" DBH W.Oak with a fully healed double blaze bears S.33½°E., 409.8 ft. (as per record)  
1964 BT, a 13" W.Oak now an 18" DBH W.Oak with a fully healed double blaze bears S.27½°E., 389.1 ft. (as per record.)  
The position of the witness corner as established in 1964 is perpetuated by placing a new monument directly above the found brass cap monument. The new monument is a 2 3/8" dia. brass cap marked: "Douglas County Surveyors Office T22S North 55 ft. to cor. WC DLC 44 43 DLC RESET R8W 1987", on a 1" I.D. 32" long iron pipe, set protruding 5" from ground.  
New BT - A 9" DBH Ash double blaze and scribed "NW DLC 43 CS BT" growing from NE edge of a 36" dia. 2 ft. tall Ash stump bearing and dist. are measured to base of trunk of 9" DBH Ash where it grows from stump. 9" Ash bears N.50°E., 139.4 ft.  
Monument is at top of high South bank of the Umpqua River in an old North-South fence line.

Fd. OK, Jan. 1994 - M 120-49 A&B  
Fd. OK, May 1995 - M 122-62  
Found OK by M. Smalley, Dec. 2000 - M132-59