

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 044100

PRIMARY CORNER DESCRIPTION SW Cor. Wm. Hathaway DLC 44

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Surveys of Donation Land Claims by - Dennis Hathorn, Deputy,  
dated Sept. 1856

-----  
Marked a Fir 36" dia. for the SW cor. Claim 44, from which  
A Fir 36" dia., bears N.25°E., 19 lks.  
A Fir 36" dia., bears S.88°W., 14 lks.

Douglas Co. Surveyors Office - James Byron, Deputy - Feb.  
1955 - C.S. File 46/125 and M 8-18

-----  
Found - A 4 ft. Fir snag, bark scribed C 44 on NE face. I  
use this tree for original corner.  
Also find 30" Fir stump which bears S.88°W., 9.2  
ft., bark scribed 4 at top of cut.  
Set an Iron pipe with brass cap 3 ft. East of center of 4 ft.  
snag, mkd. "W.C. 3 feet West to S.W. corner D.L.C. 44 T22S  
R8W County Surveyors Office, 1955"  
Blazed and scribed:  
14" R.Fir N.28°W., 27.0 ft. mkd. W.C. SW Cl 44 T22S  
R8W.  
8" R.Fir S.44½°W., 14.2 ft. mkd. W.C. SW Cl 44 CS BT

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike  
Stone & Vernon "Ray" Tracy, crew - Dec. 1962/Jan. 1963 - C.S.  
File 52/14-70

-----  
Found - DCSO brass cap set in 1955.  
The 14" D.Fir N.28°W., 27.0 ft. still alive and in  
good condition.  
The SW BT mkd. in 1955 is now dead, down and rotting  
New BT - 16" Fir S.49°W., 25.9 ft. mkd. WC SW DLC 44 CS BT.

BLM resurvey by Floyd Brooks and Peter Peterson, Cadastral  
Surveyors - under Group #'s 595 and 657 - surveyed Aug.  
1965/Dec. 1967 - (DCSO records Vol. 34 Page(s) 14124-25)

-----  
The SW cor. DLC #44 on the E. bdy. of DLC #45, monumented  
with a decayed Fir stump 40" dia., with fragmentary scribe  
marks visible on badly scaled bark blaze, from which the  
original bearing trees:  
A sawed and decayed Fir stump, 40" dia., bears N.25°E., 19  
lks. dist. with fragmentary scribe marks visible on  
pitch splinter pulled loose from decayed wood near  
center of stump.  
A sawed and decayed Fir stump 39" dia., bears S.88°W., 14  
lks. dist. no marks remaining.  
and bearing tree and witness cor. established by the County  
in 1955: (Cont. Next Page)

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 044100

PRIMARY CORNER DESCRIPTION SW Cor. Wm. Hathaway DLC #44

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

A sawed Fir stump 14" dia., bears N.28°W., 41 lks. dist. with fragmentary scribe marks visible on nearly healed blaze.

An iron post 1" dia., firmly set, projecting 16" above ground, bears East, 5 lks. dist. with brass cap marked:

COUNTY SURVEYORS OFFICE  
WC 3' WEST TO SW COR. DLC 44  
T 22 S  
1955  
R 8 W

and a bearing tree marked by the County in 1963

A sawed Fir stump 16" dia., bears S.49°W., 39 lks. with fragmentary scribe marks visible on nearly healed blaze and new bearing trees:

A Fir 10" dia., bears N.4°E. 112 lks. mkd. T22S R8W C44 BT

A W.Fir 5" dia. bears S.40°E. 70 lks. mkd. T22S R8W S28 BT

The cor. is located in fence line extending N. and S.

Fd. OK, May 1995 - M 122-62

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike  
- 6/14/2006 - C.S. File 67/14-23

Found - BC/IP witness monument found laying on top of ground on side partially buried. (Properly marked)  
Orig. corner tree now completely rotted away.  
Base of loose BC/IP bears N.68°E., 2.7 ft. from calculated position of center of root crown.  
10" dia., Fir (1965) now 34" dia., x 2½ ft. tall  
D.Fir stump. No evidence of scribing since face portion of stump was cut off in the fasion of a seat bears N.4°E., 73.9 ft. (agrees w/rec.)  
5" dia., W.Fir (1965) now 18" dia., x 2 ft. tall rotting stump evid. of healed blaze bears S.40°E., 46.2 ft. (agrees w/rec)  
36" dia., Fir (1856) now very rotted 40" dia., x 4 ft. tall stump. Center of mass bears N.25°E., 12.5 ft. (agrees w/rec.)

No trace of any other BTs found.

New - BC/IP was set in place using record data from found accessories. BC is 2½" dia., x 32" long on a 1¼" dia., IP projects 9" above ground, mkd:

DOUGLAS COUNTY SURVEYORS OFFICE

T22S R8W

SW

DLC 44

2006

NO LONGER A WITNESS CORNER

cont. next page

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 044100

PRIMARY CORNER DESCRIPTION SW Cor. Wm. Hathaway DLC 44

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

14" dia., D.fir double blazed & scribed "SW DLC 44 CS BT" bears S.21°W., 58.0 ft.  
Double trunk wild cherry, southerly trunk is 9" dia., & is scribed "SW DLC 44 CS BT" bears N.22°E., 7.1 ft.  
BC/IP dated 1965 at SE cor. DLC 45 bears South 66.0 ft.

Note - Corner lies 1 ft. east of N-S fence with hayfield to west and young timber plantation of east.  
Compass decl. 16½°E.