

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 044110

PRIMARY CORNER DESCRIPTION S SE cor. Wm. Hathaway DLC #44

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Surveys of Donation Land Claims by - Dennis Hathorn, Deputy,
dated Sept. 1856

Set post for corner, from which
A Fir 15" dia., bears N.15°W., 17 lks.
A Maple 24" dia., bears S.20°E., 20 lks.

Douglas Co. Surveyors Office - James Byron, Deputy - Feb.
1955 - C.S. File 46/125 and M 8-18

Corner located by proportional method. No evidence of "L"
corners found - the call for creek checks.
Set an Iron post with brass cap at cor. mkd: Co. Su. Off.
1955, Ext L Cl 44 T22S R8W.
Blazed and scribed
10" R.Fir N.9°W., 4.6 ft. mkd. Cl. Ext L Cl 44 CS BT.
8" R.Fir S.88½°E., 47.9 ft. mkd. Cl Ext. L Cl 44 CS BT.

Cor Fd in good condition, Sept. 1964, DCSO C.S. File 52/14-88

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike
- 4/13/2006 - C.S. File 67/14-12

Found - 2½" BC on 1¼" O.D. IP, (properly mkd) firmly set
projects 8" above ground.
Orig. 10" R.Fir now 26"x12" high rotting stump bears
S.9°E., 4.6 ft. (agrees w/rec.) 1955 BT
No trace of 1955 SE BT FD.
New - 23" dia., maple double blazed & scribed "S SE DLC 44
CS BT" bears S.34½°E., 78.0 ft.
7" dia., W.Fir double blazed & scribed "S SE DLC 44
CS BT" bears N.56½°E., 11.0 ft.
5" dia., D.Fir double blazed & scribed "X BT" bears
S.70°W., 21.4 ft.
11" dia., pistol butt maple double blazed & scribed
"S SE DLC 44 CS BT" bears North, 61.3 ft.
Note - Corner lies on nearly level bench above creek.
Center of creek bears South approx. 55 ft. flows
N.20°W.
Compass decl. 16¼°E.