

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 047050

PRIMARY CORNER DESCRIPTION SW Cor. Abel Fryer DLC #47 WIT. COR.

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Surveys of Donation Land Claims by - Dennis Hathorn, Deputy,  
dated Sept. 1856

-----  
Intersect W. bdy. sec. 16 and set post SW cor. Claim 47, from  
which

An Alder 18" dia., bears S.74°W., 30 lks.

An Alder 15" dia., bears S.16°E., 38 lks.

F. C. Frear, Deputy Co. Surveyor - Wit: Chas. Clements and  
F.B. Soloman - Sept. 1917 - Field Book 43 Page 12

-----  
Renew from old BTs.

Set in a 1½" x 40" Iron pipe, from which

A 12" W.Oak bears N.82°E., 90 lks. dist.

A 12" W.Oak bears N.71½°E., 81 lks. dist.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike  
Stone & Vernon "Ray" Tracy, crew - Dec. 1962/Jan. 1963 - C.S.  
File 52/14-50

-----  
Found - 16" W.Oak N.82°E., 59.4 ft., cut open and found  
portion of scribe. (Frear, 1917)

16" W.Oak N.71½°E., 53.5 ft., cut open and found  
good scribing "S". (Frear, 1917)

Did not find pipe set by Frear or original BT.

Corner position falls in creek.

Set WITNESS CORNER 15 ft. East of DLC cor.

Set Brass mkd: County Surveyors Office

T 22 S R 8 W

W.C. SW. DLC 47|\_\_

1962

New BTs -14" D.Fir S.82°W., 6.7 ft. mkd. WC SW DLC 47 CS BT

11" D.Fir S.71°E., 61.5 ft. mkd. WC SW DLC 47 CSBT

BLM resurvey by Floyd A. Brooks and James E. Jelley,  
Cadastral Surveyors, under Group #'s 514 and 350, surveyed  
June 1963/March 1965 (DCSO records Vol. 33 Page(s) 13696)

-----  
(Corner report)

True point for the SW. cor. of DLC #47, which falls in a  
creek 2 lks. wide, course S.35°E., perpetuated and recorded  
by Frear in 1917, when the original bearing trees were  
existent; from which the trees mkd. by Frear:

An Oak 16" dia., bears N.71½°E., 81 lks. dist., with  
partial scribe marks visible on opened blaze.

An Oak 16" dia., bears N.82°E., 90 lks. dist., with healed  
blaze.

(Cont. Next Page)

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 047050

PRIMARY CORNER DESCRIPTION SW Cor. Abel Fryer DLC #47

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

From this point, at witness corner established by Fred Darby, Co. Surveyor in 1962, bears East, 23 lks. dist., monumented with an iron post, 1½" dia., 10" above ground, firmly set, with brass cap marked: COUNTY SURVEYORS OFFICE

T 22 S  
W | D L C  
C | 47 R 8 W  
SW

15 ft. to cor.  
1962

from which bearing trees mkd. by Darby:

A Fir 10" dia., bears S.74°E., 93 lks. dist., with scribe marks W C SW DLC CS 47 BT visible on open blaze.

A Fir 14" dia., bears S.78°W., 10½ lks. dist., with scribe marks WC SW DLC 47 CS BT visible on open blaze.

Bruce Shaner, surveyed for - Ronald & Annie Meints; June-July 1996 - M 125-25 & CS 65/8-1A

Found - 1962 D.C.S.O. Brass Cap w/iron pipe  
24" D.Fir BT stump w/face overgrown, bears S.74°E., 61.5'  
30" D.Fir BT, face overgrown, bears S.78°W., 6.9 ft.

New Accessories -

5" D.Fir BT, I scribed "WC DLC BT" bears N.20°E., 22.6 ft.

6" D.Fir BT, I scribed "WC DLC BT" bears S.69°E., 49.1 ft.

6 foot steel fence post bears due east, 1.0 ft. of corner.

Note - True D.L.C. corner falls in creek which flows S.35°E.

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2180 & 2300, surveyed May/Oct. 2007 (DCSO records Vol. 56 Page(s) 22231-2)

The True Point for the SW. cor. of DLC 47, on the N. bdy. of DLC 46, on the line bet. secs. 16 and 17, perpetuated by Frear in 1917, and subsequently perpetuated by Godfrey in 1962-63 by establishing a witness corner to reference the true point monumented by Frear that had been destroyed by a creek, accepted by Brooks and Jelley in 1963-65, determined at record bearing and distance from the witness corner; the true point is located in a natural ditch, 3 ft. deep, 1 ft. wide, course S. 40° E., where it is impractical to establish a permanent monument, from which the remains of the bearing trees mkd. by Frear and reported by Brooks and Jelley

A roothole bears N.71½°E., 53.5 ft., alongside of which is a down oak, 14" dia., with axe marks visible on open decayed blaze with a woven wire fence grown into the tree.

continued next page

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 047050

PRIMARY CORNER DESCRIPTION SW Cor. Abel Fryer DLC #47 WIT. COR.

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

An oak, 19" dia., bears N.82°E., 59.4 ft., with a healed blaze.

From this point, the witness corner established by Godfrey and accepted by Brooks and Jelley, bears East, 15.18 ft.; monumented with an iron post, 1½" dia., firmly set, projecting 4" above ground, with brass cap (properly) mkd. from which the remains of the bearing trees mkd. by Godfrey and reported by Brooks and Jelley

A decayed fir stump, size indeterminate, bears S.71°E., 61.4 ft., no marks visible. (Record, S.74°E.)

A fir stump, 33" dia., bears S.78°W., 6.9 ft., with a healed blaze.

and the bearing trees mkd. by Shaner in 1996

A fir, 8" dia., bears N.22¼°E., 21.8 ft., with a healed blaze.

A fir, 12" dia., bears S.67¾°E., 49.6 ft., with a healed blaze.

A steel fence post is alongside the witness corner.

Corner is located on a gentle SE. slope, at the SE. cor. of fir reproduction, edge bears N. and W., with young timber to the S. and E.