

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 049130

PRIMARY CORNER DESCRIPTION Pt. on NE. bdy. A. Sawyer DLC #49

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Surveys of Donation Land Claims by - Dennis Hathorn, Deputy,  
dated Sept. 1856

-----  
Marked a Fir 24" dia., for cor., from which  
An Oak 20" dia., bears S.2°W., 50 lks.  
An Oak 12" dia., bears S.65°E., 57 lks.

BLM resurvey by Floyd A. Brooks and James E. Jelley,  
Cadastral Surveyors, under Group #'s 514 and 350, surveyed  
June 1963/March 1965 (DCSO records Vol. 33 Page(s) 13712)

-----  
The Cor. of Claim #49, on the left bank of the Umpqua River,  
perpetuated with an iron pipe, 2" dia., 10" above ground,  
firmly set. This point has long been locally accepted as the  
corner position, and is now adopted as the best available  
evidence of the original corner.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground,  
with brass cap mkd:

T 22 S R 8 W  
    \    S 4  
    C 49  
    1963

from which

A Fir 12" dia., bears S.18°W., 48 lks. dist. mkd. T22S R8W  
C49 BT.

No other suitable bearing tree available.  
Reset the iron pipe alongside the iron post.