

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 054020

PRIMARY CORNER DESCRIPTION NW Cor. Daniel Test DLC #54

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Surveys of Donation Land Claims by - Dennis Hathorn, Deputy,  
dated Sept. 1856

-----  
Set post, from which

A Fir 9" dia., bears N.28°W., 65 lks.

An Oak 9" dia., bears N.2°W., 217 lks.

BLM resurvey by Floyd A. Brooks and James E. Jelley,  
Cadastral Surveyors, under Group #'s 514 and 350, surveyed  
June 1963/March 1965 (DCSO records Vol. 33 Page(s) 13712)

-----  
At the NW cor. of Claim No. 54 in sec. 28, which is  
perpetuated by the cor. of old barbed and woven wire fences  
extending north, east, and south. This point has long been  
accepted by local property owners as the true point for the  
NW. cor. It is now adopted as the best available evidence of  
the corner position.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground,  
with brass cap mkd: T 22 S R 8 W

S 28 | C 54  
1964

from which

A Fir 23" dia., bears N.9¼°W., 218 lks. dist. mkd. T22S  
R8W S28 BT.

A Fir 6" dia., bears S.10½°W., 197 lks. dist. mkd. T22S  
R8W S28 BT.

Douglas Co. Surveyors Office - Randall Smith and Stephen  
Flause, crew - Oct. 7, 1986 - C.S. File 62/37-2

-----  
Found - 23" now 39" dia. D.Fir with a fully healed single  
blaze, opened and scribing found "22S R8W", bears  
N.9¼°W., 142.0 ft. (rec. N.9¼°W., 143.9 ft. is a  
slope dist.)

6" now 12" dia. 3 ft. high D.Fir stump with a fully  
healed single blaze, opened and scribe found "8"  
bears S.10½°W., 130.0 ft.

Brass cap on iron pipe gone, recent logging in area.

Set a DCSO brass cap on a 1 3/8" O.D. x 32" I.P., protrudes  
5" above ground and marked: Douglas County Surveyors

T22S S28 | C 54  
R8W 1986.

Monument set from 1964 BLM BTs at record bearing and distance  
to SW BT and rec. bearing and a slope dist. to NW BT.

(Cont. Next Page)

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 054020

PRIMARY CORNER DESCRIPTION NW cor. Daniel Test DLC #54

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Position falls in old wire woven fence and wood post uncovered. Wire orientated N-S.

New Accessories:

Boat spike set in top center of 12" dia. 3 ft. high  
D.Fir stump. (SW BT) stamped "DCSO 1986", bears  
S.10½°W., 130.0 ft.

21" dia. D.Fir double blazed and scribed "NW DLC 54  
CS BT" bears N.29½°E., 155.0 ft.