

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION SW Cor. Sec. 31 (SW Tsp. Cor.)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 376 survey dated Jan. 22, 1881 (DCSO records Vol. 4 Page(s) 1594)

Set Hemlock post for Tp. cor., from which
 A Fir 34" dia., bears N.65°W., 118 lks. dist.
 A Fir 60" dia., bears N.70°E., 137 lks. dist.
This point was obtained by running a line South on West bdy. without chaining.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone & Vernon Tracy, crew - March 1963 - C.S. File 52/14-75

Found - 1½" Iron pipe (galv.) and wooden stake.
 54" Fir N.65°W., 77.9 ft., old uproot, dead. Found bark scribing.
 72" Fir N.70°E., 90.4 ft., old, dead, uproot, bark charred and covered with mud. No scribing found.
Did Not Set Brass Cap. I.P. in good condition.
New BTs -9" D.Fir N.68°E., 45.8 ft. mkd. T22S R8W S31 CS BT.
 20" D.Fir N.66°W., 25.0 ft. mkd. T22S R9W S36 CSBT.
 D. Fir S.89°W., 30.4 ft. mkd. T23S R8W S6 CSBT.
Corner lies on steep NE. slope.

Fd. OK, VRT, DCSO, Feb. 1967 C.S. File 54/12-65A

BLM resurvey by Harvey E. Wofford, Cadastral Surveyor, under Group #1005, surveyed July/Sept. 1980 - (DCSO records Vol. 43 Page(s) 16779-80)

The cor. of Tps. 22 S., Rs. 8 and 9 W., perpetuated and recorded by Godfrey in 1963, monumented with an iron pipe, 1½" dia., firmly set, projecting 8" above ground, from which the remains of an original bearing tree:

 A roothole bears N.70°E., 137 lks. dist. alongside of which is a downed, decayed Fir, 72" dia., no marks visible.
and bearing tree mkd. by Godfrey:
 A Fir 13" dia., bears N.68°E., 69½ lks. dist. with healed blaze.
 A Fir 16" dia., bears S.89°W., 46 lks. dist. with healed blaze.
 A Fir 26" dia., bears N.66°W., 38 lks. dist. with healed blaze.

At the corner point
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd: (Cont. Next Page)

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION SW Cor. Sec. 31 (SW Tsp. Cor.)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

T 22 S
R 9 W R 8 W
S 36 | S 31
T 23 S R 8 W S 6
1980

Deposit the iron pipe alongside the iron post.

From this point, the true point for the NW. cor. of T23S R8W bears S.89°51'W., 8.60 chs. dist.

Fd. OK, Jan. 13, 1983 by R. Luckman, M 93-41
