

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 100140

PRIMARY CORNER DESCRIPTION W. 1/4 Corner Sec. 31 only

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 202 survey dated March 11, 1874 (DCSO records Vol. 4 Page(s) 1594)

Set Fir post for ¼ sec. cor., from which
A Fir 30" dia., bears N.23°E., 29 lks. dist.
A Fir 30" dia., bears S.65°W., 20 lks. dist.

BLM survey by Harvey E. Wofford, Cadastral Surveyor, under Group #1005, surveyed July/Sept. 1980 - (DCSO records Vol. 43 Page(s) 16780)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:
T 22 S
R 9 W R 8 W
¼ S 31
1980

from which
A Grand Fir 4" dia., bears N.82½°E., 9 lks. dist. mkd. X BT.
A Fir 6" dia., bears S.10½°E., 21 lks. dist. mkd. ¼ S31 BT

Survey by Rockne Luckman - For: International Paper Co. - Jan. 13, 1983 - M 93-41

CORNER REPORT ONLY

Found - Apparent 1980 BLM BC and BTs. (no record)
6" D.Fir bears S.½°W., 13.4 ft. (Rec. S.10½°E)
4" W.Fir bears N.78°E., 5.4 ft.

Fd. and used in BLM sec.subd. survey by Joel E. Robb, Cadastral Surveyor, under Group #1166 - surveyed July/Aug. 1983 (DCSO records, Vol. 46 Pages 17797-98)