

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 100240

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. Sec. 30 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 202 survey dated March 11, 1874 (DCSO records Vol. 4 Page(s) 1595)

-----  
Set post for ¼ sec. Cor. From which  
A fir, 8" dia., bears N.2°E., 27 lks.  
A fir, 6" dia., bears S.3°W., 15 lks.

Douglas County Surveyors Office - Milo E. Godfrey, Deputy - C.S. File 52/14-131 - Jan. 1963

-----  
Corner searched for, not found.

BLM survey by Floyd Brooks and Peter Peterson, Cadastral Surveyors - under Group #'s 595 and 657 - surveyed Aug. 1965/Dec. 1967 (DCSO records Vol. 34 Page(s) 14106)

-----  
At record distance for the ¼ sec. cor. of sec. 30 only; there is no remaining evidence of the original corner.

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2149, surveyed Aug. 2006/Oct. 2006 - (DCSO records Vol. 55 Page(s) 21729)

-----  
Point for the 1/4 sec. cor. of sec. 30 only, at proportionate distance; there is no remaining evidence of the original cor. Not monumented.