TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 100246

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. Sec. 25 only, T22-9

Alias_____ Description_____
Alias_____ Description_____
Alias_____ Description_____
Alias_____ Description_____

BLM resurvey by Floyd A. Brooks and Peter A. Peterson, Cadastral Surveyors, under Group #'s 595 and 657 - surveyed Aug. 1965/Dec. 1967 - (DCSO records Vol. 34 Page(s) 14106-07)

Point for the ¼ sec. cor. of sec. 25 only, T22S R9W.
Set an iron post 28" long, 2½" dia., 24" in the ground, with brass cap mkd: ¼

T 22 S |
R 9 W |
S 25 |
1965

from which
An Alder 8" dia., bears N.65°W., 66 lks. dist. mkd. ¼ S25 BT.
A Maple 20" dia., bears S.13°W., 57 lks. dist. mkd. ¼ S25 BT.
Corner falls on S. bank of creek.

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2149, surveyed Aug. 2006/Oct. 2006 - (DCSO records Vol. 55 Page(s) 21729)

The ¼ sec. cor. of sec. 25 only, determined at record bearing and distance from the bearing tree mkd. by Brooks and Peterson in 1965-67
A maple, 23" dia., bears S.13°W., 37.6 ft., with a healed blaze.
At the corner point
Set a stainless steel post, 28" long, 2½" dia., 20" in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.

T 22 S|
R 9 W|
¼ S 25|
2006

from which a new reference monument
A stainless steel post, 28" long, 2½" dia., set 25" in the ground for a reference monument, bears North, 45.00 ft. with brass cap mkd. RM T22S R9W ¼ S25 45 FT 2006 and an arrow pointing to the corner. Post is located S., 20 ft. from Lutsinger Creek Road.
Deposit a magnet in a white plastic case at the base of both stainless steel posts.
Corner is located at the base of the S. cutbank of Lutsinger Creek.