

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Sec. cor. for 19 & 30; 24 & 25, T22-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, the westerly of two growing together, 24" dia., bears N.19°W., 13.9 ft., with a healed blaze.
No suitable trees to the E. available.
Corner is located on the W. edge of fir reproduction, edge bears N. and S.

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2180 & 2300, surveyed May/Oct. 2007 (DCSO records Vol. 56 Page(s) 22221)

The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., reestablished by Brooks and Peterson in 1965-67; monumented with an iron post, 2½" dia., firmly set, projecting 8" above ground, with brass cap (properly) mkd. from which the remains of the bearing trees mkd. by Brooks and Peterson

A decayed fir stump, 19" dia., bears N.78¼°E., 47.5 ft., no marks visible.

A fir stump, 21" dia., bears S.43°E., 24.4 ft., with a healed blaze.

A fir, 16" dia., bears S.38°W., 14.9 ft., with a healed blaze and snow blaze.

A fir, the westerly of two growing together, 24" dia., bears N.19°W., 13.9 ft., with a healed blaze.

No suitable bearing trees available to the E.

Corner is located on a SE. slope on the W. edge of fir reproduction, edge bears N. and S.

The geographic position (NAD 1983 (CORS 96)) of the corner of sections 19, 24, 25, and 30, on the west boundary of the township, as determined by a tie from a temporary GPS control point, established utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's Online Positioning User Service (OPUS), is as follows:

Latitude: 43°38'10.28"N. Longitude: 123°42'18.39"W.