TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 100434

PRIMARY CORNER DESCRIPTION A.P. 1 bet. secs. 18; & 13, T22-9

Alias Description
Alias Description
Alias Description
Alias Description

GLO survey by Geo. F. Rigby, U.S. Cadastral Engineer, under Group #143, surveyed Oct/Nov. 1931 - (DCSO records Vol. 27 Page(s) 11648)

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for angle point No. 1, with brass cap mkd: A P 1
S 13 /
S 18
1931

from which

A Fir 44" dia., bears N.18°30'E., 34 lks. dist. mkd. A P 1 S18 BT.

A Maple 15" dia., bears S.71°W., 21 lks. dist. mkd. A P 1 S13 BT.

BLM resurvey by Floyd A. Brooks and James E. Jelley, Cadastral Surveyors, under Group #'s 514 and 350, surveyed June 1963/March 1965 (DCSO records Vol. 33 Page(s) 13731-32)

The angle point bet. secs. 13 and 18, monumented with an iron post, 1" dia., firmly set, projecting 8" above ground with 1931 brass cap.

from which bearing trees mkd. by Rigby

A rotted Fir stump 46" dia., bears N.18½°E., 34 lks. dist. with no marks remaining.

A Maple 18" dia., bears S.71°W., 21 lks. dist. with a healed blaze.

Add a new bearing tree

A Hemlock 10" dia., bears N.30½°E., 59 lks. dist. mkd. AP 1 S18 BT.