

PRIMARY CORNER DESCRIPTION Sec. cor. for 7 & 18; 12 & 13, T22-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 202 survey dated March 11, 1874 (DCSO records Vol. 4 Page(s) 1588)

-----

Set a granite stone, 18x10x6 ins. in ground for cor. to secs. 7, 12, 13 and 18, from which  
 An Alder 10" dia., bears N.47°W., 181 lks. dist.  
 No other trees near.

GLO resurvey by Geo. F. Rigby, U.S. Cadastral Engineer, under Group #143, surveyed Oct/Nov. 1931 - (DCSO records Vol. 27 Page(s) 11649)

-----

The point of the original cor. of secs. 7, 12, 13 and 18, monumented with a granite stone, 10 x 10 ins., 8" above ground, with no visible marks. In place of the stone Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

T 22 S	
R 9 W	R 8 W
<u>S 12</u>	<u>S 7</u>
S 13	S 18
1931	

from which:  
A rotted Alder stump 18" dia., bears N.47°W., 181 lks. dist. with marks all rotted away.

New Bearing trees:

- A Fir 12" dia., bears S.20°30'E., 193 lks. dist. mkd. T22S R8W S18 BT.
- A Maple 20" dia., bears N.12°E., 59 lks. dist. mkd. T22S R8W S7 BT.
- A Fir 18" dia., bears S.85°W., 53 lks. dist. mkd. T22S R9W S13 BT.
- A Maple 20" dia., bears N.40°W., 73 lks. dist. mkd. T22S R9W S12 BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone, crew - Sept. 11, 1963 - C.S. File 52/14-71

-----

Found - Brass cap set in 1931 in good condition.  
 33" Maple N.12°E., 38.9 ft., good axe scars visible.  
 30" Fir S.85°W., 35.0 ft., scars plainly visible.  
 Tree partially dead.  
 30" Maple N.40°W., 48.2 ft. Tree in poor condition, but no other trees available to NW.  
 SE tree is gone, no trace found.

New BTs -14" D.Fir S.45°E., 102.7 ft. mkd. T22S R8W S18 CSBT.  
 15" D.Fir S.64°W., 55.5 ft. mkd. T22S R9W S13 CS BT.

Cont.

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION Sec. cor. for 7 & 18; 12 & 13, T22-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>Fd. OK, August 1991, H. Wilcox, M 113-60 FD. OK, June 1997, D. Edwards, M 127-17</p>
<p>Fd. &amp; used in BLM dependent resurvey by Boyd W. Peterson, Cadastral Surveyor, and Richard L. Sanford, Surveying Technician, under Group No. 1704, surveyed July 1993 thru June 1995 (DCSO records Vol. 52 Page(s) 19715)</p>
<p>BLM remonumentation by Aaron M. Graham, Cadastral Surveyor and Michael O. Jones Surveying Technician, under Group #2199, surveyed April 2008/April 2009 - (DCSO rec. Vol. 56 Pg 21934)</p> <p>-----</p> <p>The cor. of secs. 7, 12, 13, and 18, remonumented by Rigby in 1931; monumented with an iron post, 2" dia., firmly set, projecting 10" above ground, with a brass cap (properly) mkd. from which the remains of the BTs mkd. by Rigby in 1931</p> <p>    A maple, 27" dia. bears N.12°E., 38.9 ft. no marks visible</p> <p>    A fir, 43" dia. bears S.85°W., 35.0 ft with a healed blaze</p> <p>    A decayed maple stump, size indeterminate, bears N.40°W., 48.2 ft., no marks visible.</p> <p>and the remains of the bearing trees mkd. by Godfrey in 1962-63 and reported by Peterson in 1993-95</p> <p>    A fir, 48" dia., bears S.44°E., 103.0 ft., with a healed blaze.</p> <p>    A fir, 38" dia., bears S.64½°W., 54.8 ft., with a healed blaze.</p> <p>The geographic position (NAD 1983 (2007)) of the corner of sections 7, 12, 13, and 18 on the West boundary of the Township, as determined by a tie from a temporary GPS control point, established utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's Online Positioning User Service (OPUS), is as follows:</p> <p>Latitude: 43°39'53.95"N.      Longitude: 123°42'19.43"W.</p>
<p style="text-align: right;">2</p>