

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 100640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 6; & 1 of T22-9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 202 survey dated March 11, 1874 (DCSO records Vol. 4 Page(s) 1588-89)

Set fir post, 40" long, 5" dia., for the ¼ cor. from which:
A maple, 14" dia., bears N.70°E., 20 lks.
A fir, 5" dia., bears N.55°W., 46 lks.

GLO resurvey by Elmer O. Worrick, Deputy Surveyor, under Group #632, dated April 28, 1894 - (DCSO records Vol. 4 Page(s) 1614) (and page 1702, duplicates of Pg. 1613)

The ¼ sec. cor. As the old post was badly decayed,
Set fir post, 4½' long, 4" sq. 24" in the ground on steep hillside sloping South, marked ¼ S on the West face, from which:
A maple, 14" dia., bears N.70°E., 20 lks., marks grown over.
A fir, 5" dia., bears N.55°W., 46 lks. marks grown over.

Douglas Co. Surveyors Office - Milo E. Godfrey - Sept. 23, 1963 - C.S. File 52/14-129

Searched for, no trace found.

Victor McLind - For: Menasha Corp. - Oct. 1997 - M 127-77

Set - 2"x36" I.P. with 2" BC marked: T22
 R9W|R8W
 S1|S6
 1997
 LS 934 from which:
15" D.Fir, bears S.86°W., 24.5', blazed & scribed: "¼
 S1 BT"
12" D.Fir, bears N.42°W., 22.8', blazed & scribed: "¼
 S1 BT"
28" D.Fir, bears N.86°E., 24.1', blazed & scribed: "¼
 S6 BT"
19" D.Fir, bears S.10°W., 54.1', blazed & scribed: "¼
 S1 BT"

Corner is about 20 feet southerly of old road, and about 100 feet easterly from the easterly edge of a large slide. Note -Dist. measurements to BTs established during this survey are to a spike set in the side center of the tree. Bearings are by hand compass to the center of the tree. A tag was attached to the tree facing the corner. The line between sections 1 & 6 was marked and by blazing and orange paint.