

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 120420

PRIMARY CORNER DESCRIPTION SW 1/16 Cor. Section 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Geo. F. Rigby, U.S. Cadastral Engineer, under Group #143, surveyed Oct/Nov. 1931 - (DCSO records Vol. 27 Page(s) 11655-56)

At point of intersection with the E. and W. center line of the SW ¼ of sec. 18,
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for SW 1/16 sec. cor., with brass cap mkd: SW 1/16 S 18
1931

from which
A Fir 20" dia., bears N.76°W., 16 lks. dist. mkd SW 1/16 S18 BT.
A Fir 20" dia., bears S.42°W., 67 lks. dist. mkd SW 1/16 S18 BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone & Vernon "Ray" Tracy, crew - March 1963 - C.S. File 52/14-59

Found - Govt. brass cap set in 1931.
28" W.Fir S.42°W., 44.2 ft., shows good axe scar.
Rotted remnants of W.Fir stump N.76°W., 10.6 ft., too far gone to find any markings.
Reblaze and scribe:
28" W.Fir S.42°W., 44.2 ft. mkd. "SW 1/16 S18 CS BT."
New BT - 31" D.Fir N.11°E., 25.5 ft. mkd. "SW 1/16 S18 CS BT."