

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 128500

PRIMARY CORNER DESCRIPTION M. C. So. bdy. Sec. 7

Alias <u>939040</u>	Description <u>M.C. Right bank Umpqua River</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1579)

Set meander post on right bank of river, from which
A Cottonwood 20" dia., bears S.27°W., 23 lks. dist.
An Ash 6" dia., bears N.45°E., 31 lks. dist.

GLO survey by Geo. F. Rigby, U.S. Cadastral Engineer, under Group #143, surveyed Oct/Nov. 1931 - (DCSO records Vol. 27 Page(s) 11650 and 11653-54)

(Page 11650)
Right bank of Umpqua River. No trace of the original meander cor.

(Pages 11653-54)
50.59 chs. Proportionate point for the meander cor. of fracl. secs. 7 and 18, falls in the edge of the water on a large bar of exposed bedrock.

52.29 chs. Mean high water line of the right bank of Umpqua River

Set an iron post, 3 ft. long, 1" dia., on exposed bedrock, supported by a mound of stone, 10 ft. base, 3 ft. high, for witness meander cor. of fracl. secs. 7 and 18, with brass cap mkd:

T 22 S
 S 7 /
 S 18 / MC WC
R 8 W /
 1931

from which

An Oak 20" dia., bears N.26°45'W., 93 lks. dist. mkd. W C T22S R8W S7 MC BT.

An Alder 10" dia., bears S.65°30'W., 163 lks. dist. mkd. W C T22S R8W S18 MC BT.

Douglas County Surveyors Office - Milo E. Godfrey, Deputy - C.S. File 52/14 - Sept. 13, 1963

Corner searched for, not found.